

Thus, as the number of compatible models has increased, setup operations have become so complicated that operators must accurately identify models that are to be controlled and must then refer to operation

manuals to set up remote controllers, so that the likelihood is great that operators will mistake when they perform setups. And when the models that are to be controlled are changed frequently, the setup must be repeated often and usability will be deteriorated.

The devices that are to be controlled by such remote controllers are limited to those that are located that they are inside the effective range of the control signals emitted by the remote controllers.

SUMMARY OF THE INVENTION

To resolve the above shortcomings, it is one objective of the present invention to provide an information processing apparatus that can easily control a variety of devices, and a system therefor.

It is another objective of the present invention to provide a remote control apparatus that can easily cope with a plurality of devices without a series of complicated setups being required of a user and that can control the devices from a remote location, and a system therefor.

It is an additional objective of the present invention to provide a remote control system that can control, via a nearby device, a device in a remote location to which instructions can not be directly transmitted.

It is a further objective of the present invention

to provide an information processing apparatus that can, as needed, determine an appropriate process to be performed, such as communication with another device, and can then perform the process.

5 It is still another objective of the present invention to provide an information processing apparatus that can acquire, from another device, information that it is to process, and can then process the information.

10 It is a still additional objective of the present invention to provide an information processing apparatus that can transmit information, such as an instruction that is the result obtained from a process it performed, to another device for storage at that
15 device.

 It is a still further objective of the present invention to provide an information processing apparatus that can control another device by employing an operation unit that controls the information
20 processing apparatus.

 The other objective of the present invention is to provide an information processing apparatus that can flexibly cope with changes in the operational procedures.

25 According to one aspect, the present invention which achieves these objectives relates to a remote control apparatus comprising:

reception means for receiving information concerning a device to be controlled;

validation means for validating operating procedures for the device to be controlled; and

5 transmission control means for transmitting an operating command to the device based on the operating procedures that are validated.

According to another aspect, the present invention which achieves these objectives relates to a remote system comprising:

10 identification means for identifying a device to be controlled by a remote control apparatus; and

transmission control means for transmitting to the remote control apparatus information concerning a device that is identified,

15 wherein the remote control apparatus transmits an operating command to the device in accordance with operating procedures based on the information that is received.

20 According to yet another aspect, the present invention which achieves these objectives relates to a remote control apparatus comprising:

input means for receiving an instruction;

processing means for performing processing in accordance with the instruction input by the input means;

communication means for communicating with another

5

10

15

20

25

control means for permitting the processing means to process the information acquired by the acquisition means.

According to yet one more aspect, the present invention which achieves these objectives relates to an information processing apparatus comprising:

communication means for communicating with an
5 external device;

processing means for processing information from the external device that is received through the communication means;

transmission control means for transmitting to the
10 external device through the communication means the information that is processed by the processing means; and

control means for storing in the external device the information that has been transmitted to the
15 external device through the communication means.

According to still one more aspect, the present invention which achieves these objectives relates to an information processing apparatus comprising:

operating means for performing an operation;

20 input means for inputting information;

processing means for, based on the operation, processing the information input by the input means;

output means for outputting results obtained by the processing means; and

25 control means for controlling another device based on an operation for the device performed by the operation means.

a determination step of specifying a process to be
5 performed by an information processing apparatus; and

According to yet an additional aspect, the present invention which achieves these objectives relates to an information processing method comprising:

15 an acquisition step of acquiring information
through the communication unit from the external
device; and

According to still another additional aspect, the present invention which achieves these objectives relates to an information processing method comprising:

25 a processing step of processing information;
 a transmission step of transmitting the
information that has been processed at the processing
step to an external device through a communication

unit, which is used to communicate with the external device; and

5 a control step of storing in the external device the information that has been transmitted through the communication unit to the external device.

According to a further aspect, the present invention which achieves these objectives relates to an information processing method, for an information processing apparatus that has an operating unit for performing processing, comprising:

10 an input step of inputting information;
a processing step of processing, based on the operation, the information input at the input step;
an output step of outputting results obtained at
15 the processing step; and

a control step of controlling another device based on an operation performed for the device by the operation unit.

According to a still further aspect, the present invention which achieves these objectives relates to a computer-readable storage medium used to store an information processing program for controlling a computer for processing of information, the program comprising codes for enabling the computer to perform:

25 a determination step of specifying a process to be performed by an information processing apparatus; and

a processing step of performing the process

2025 RELEASE UNDER E.O. 14176

specified at the determination step.

According to one more additional aspect, the present invention which achieves these objectives relates to a computer-readable storage medium used to
5 store an information processing program for controlling a computer for processing of information, the program comprising codes for enabling the computer to perform:

a processing step of processing information that is received from an external device through a
10 communication unit, which is used to communicate with the external device;

an acquisition step of acquiring information through the communication unit from the external device; and

15 a control step of, at the processing step, processing the information that is acquired at the acquisition step.

According to yet one more additional aspect, the present invention which achieves these objectives
20 relates to a computer-readable storage medium used to store an information processing program for controlling a computer for processing of information, the program comprising codes for enabling the computer to perform:

a processing step of processing information;
25 a transmission step of transmitting the information that has been processed at the processing step to an external device through a communication

2025 RELEASE UNDER E.O. 14176

unit, which is used to communicate with the external device; and

5 a control step of storing in the external device the information that has been transmitted through the communication unit to the external device.

According to still one more additional aspect, the present invention which achieves these objectives relates to a computer-readable storage medium used to store an information processing program for controlling
10 a computer for processing of information, the program comprising codes for enabling the computer to perform:

an input step of inputting information;

a processing step of processing, based on the operation, the information input at the input step;

15 an output step of outputting results obtained at the processing step; and

a control step of controlling another device based on an operation performed for the device by the operation unit.

20 Other objectives and advantages besides those discussed above will become apparent to those skilled in the art during the course of the description of the preferred embodiments of the invention that follows. In the description, reference is made to accompanying
25 drawings, which form a part thereof, and which illustrate an example of the invention. Such example, however, is not exhaustive of the various embodiments

of the invention, and therefore reference is made to the claims that follow the description for determining the scope of the invention.

5 BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram illustrating the arrangement of an information processing system according to a first embodiment of the present invention;

10 Fig. 2 is a diagram illustrating the functional
arrangement according to the first embodiment;

Fig. 3 is a diagram illustrating the hardware arrangement of the individual units according to the first embodiment;

15 Fig. 4 is a flowchart showing the processing
performed for the first embodiment;

Fig. 5 is a diagram showing a process for selecting an optimal printer from a plurality of printers and performing a printing job with it;

20 Fig. 6 is a diagram for explaining a case where a
 controller is used;

Fig. 7 is a diagram showing a case where a document is read by a scanner for transmission to a specific printer;

25 Figs. 8, 9 and 10 are diagrams illustrating a case
where a document is read by a scanner for transmission
to a specific printer that the scanner can not control;

Fig. 11 is a diagram illustrating a case where information concerning the state of a printer is distributed;

Fig. 12 is a flowchart showing the processing performed an eighth embodiment;

Fig. 13 is a table containing remarks for determining whether or not an advance notice should be transmitted in consonance with job types and conditions;

Figs. 14A and 14B are respectively diagrams of a case where a user is informed in advance of information to be filed and a case where unnecessary information is abandoned;

Fig. 15 is a flowchart showing the processing for a ninth embodiment;

Fig. 16A is a diagram showing the transmission of information for the ninth embodiment;

Fig. 16B is a diagram showing the transmission of information when an apparatus corresponding to the object of a job is not present;

Fig. 17 is a diagram showing an example display for a window by which an optimal method is proposed to a user;

Fig. 18 is a flowchart showing the detailed procedure for job execution;

Fig. 19 is a diagram showing an example of classified information to be read;

5

10

15

20

25

Fig. 26 is a diagram showing example scheduling

Fig. 29 is an example job table;

Fig. 32 is an example job table;

Fig. 34 is an example job table;

Fig. 36 is a table for displaying planning and action rules;

Fig. 37 is a table for displaying planning and action rules;

Fig. 38 is a diagram showing actions and premise

conditions for an object;

Fig. 39 is a table for example apparatus properties;

Fig. 40 is a table for example apparatus statuses;

5 Figs. 41A and 41B are diagrams showing states where a plurality of apparatuses are connected to a network;

Fig. 42 is a diagram showing a functional arrangement for performing the processing for a
10 fourteenth embodiment;

Fig. 43 is a main flowchart showing the processing for the fourteenth embodiment;

Fig. 44 is a flowchart showing the processing for controlling other apparatuses;

15 Fig. 45 is a flowchart showing the processing performed by one's own apparatus;

Fig. 46 is a diagram showing an example where a printer other than a designated printer is employed for output;

20 Fig. 47 is a diagram showing an example where a designated printer transfers a job to another printer;

Fig. 48 is a diagram showing an example where a user's printer transfers a job to a printer at a user's destination;

25 Fig. 49 is a flowchart showing the processing for a sixteenth embodiment;

Fig. 50 is a conceptual diagram showing the

601121 220600

Fig. 51 is a diagram showing transmission of a job for a seventeenth embodiment;

Fig. 52 is a flowchart showing the processing performed by a print job automatic setup unit;

Fig. 53 is a table showing printing periods and consumption of toner for a plurality of printers for printing a single character;

Fig. 54 is a diagram showing the contents of a
10 print job and parameters designated by a user;

Fig. 55 is a flowchart showing the processing performed by a print job automatic change unit;

Fig. 56 is a diagram showing the contents of a print job and parameters designated by a user;

15 Fig. 57 is a diagram showing transmission of a job
for a nineteenth embodiment;

Fig. 58A is a diagram for explaining an example where parameters are set for a print job by employing a natural language;

20 Fig. 58B is a table showing the meanings of
character strings in the parameter setup, and request
items with which to complete the meanings;

Fig. 59 is a diagram showing an example where parameters of a print job are set by using a document;

25 Fig. 60 is a diagram showing transmission of a job
for a twenty-first embodiment;

Fig. 61 is a flowchart showing the processing

performed by a print job simulation unit;

Fig. 62 is a flowchart showing the processing performed by a printer system according to a twenty-second embodiment;

5 Figs. 63A and 63B are diagrams illustrating the external appearance of the printer system according to the twenty-second embodiment;

Fig. 64 is a flowchart showing the processing performed for a twenty-third embodiment;

10 Fig. 65 is a diagram showing the functional arrangement of a system according to the twenty-third embodiment;

Fig. 66 is a diagram showing a system for performing the overall process according to the twenty-third embodiment and input/output types relative to an external apparatus;

Fig. 67 is a diagram showing an example where a schedule is extracted from electronic mail;

20 Fig. 68 is a flowchart showing specific processing performed for the twenty-third embodiment;

Fig. 69 is a diagram showing an example schedule conflict;

Fig. 70 is a diagram showing an example where a user aurally queries a system;

25 Fig. 71 is a flowchart showing the processing for a twenty-fourth embodiment;

Fig. 72 is a diagram showing an example

Sheet "E080800"

rearrangement of conflicting schedules;

Fig. 73 is a flowchart showing the processing for re-planning conflicting schedules;

Fig. 74 is a flowchart showing the processing for re-planning responses;

Fig. 75 is a diagram showing an overall image including the input/output of a system according to a twenty-sixth embodiment;

Fig. 76 is a flowchart showing the overall processing performed by the system according to the twenty-sixth embodiment;

Fig. 77 is a flowchart showing the processing performed by an input management unit;

Fig. 78 is a flowchart showing the processing performed by a core unit;

Fig. 79 is a flowchart showing the processing performed by an output management unit;

Fig. 80 is a flowchart showing data derivation processing;

Fig. 81 is a diagram showing an example document from which data are to be extracted;

Figs. 82A and 82B are diagrams for explaining a specific block reading process;

Fig. 83 which is composed of Figs. 83A and 83B are flowcharts showing determination procedures in a process for referring to date data;

Fig. 84 is a diagram showing transmission of

2025 RELEASE UNDER E.O. 14176

Fig. 85 is a diagram showing transmission of information according to a twenty-eighth embodiment;

Fig. 86 is a diagram showing transmission of

Fig. 87 is a flowchart showing the processing for the twenty-eighth embodiment;

Fig. 88 is a table showing knowledge of a common knowledge base;

10 Fig. 89 is a table showing knowledge of a common
knowledge base in a field specified on a cover page;

Fig. 90 is a diagram showing an example where voice is used to refer to processing history to perform a process;

15 Fig. 91 is a flowchart showing the processing
performed according to a thirtieth embodiment;

Fig. 92 is a diagram illustrating an example input document;

Fig. 93 is a diagram showing the contents of a
20 conversation between a system and a user;

Fig. 94 is a diagram showing an output document that a system prepares based on the judgement of the conversation;

Fig. 95 is a flowchart for an example where a
25 required process is automatically performed after a
user is queried;

Fig. 96 is a diagram showing an example wherein a

system is operated by a controller;

Fig. 97 is a diagram showing an example status monitor;

Fig. 98 is a diagram showing an example wherein a
5 controller recognizes a target model and displays a
corresponding UI;

Fig. 99 is a flowchart showing the processing
performed by a controller for the example wherein the
controller recognizes a target model and displays a
10 corresponding UI;

Fig. 100 is a flowchart showing the processing
performed by a target model for the example wherein the
controller recognizes a target model and displays a
corresponding UI;

Fig. 101 is a diagram showing an example wherein a
15 controller receives a UI from a target model and
displays it;

Fig. 102 is a flowchart showing processing
performed by a controller for the example wherein the
20 controller receives a UI from a target model and
displays it;

Fig. 103 is a flowchart showing processing
performed by a target model for the example wherein the
controller receives a UI from the target model and
25 displays it;

Fig. 104 is a diagram showing an example wherein a
controller receives a UI from a target model via a

SECRET

wireless LAN rather than directly, and displays it;

Fig. 105 is a flowchart showing the processing performed by a controller for the example wherein the controller receives a UI via a wireless LAN and displays it;

Fig. 106 is a flowchart showing the processing performed by a target model for the example wherein the controller receives a UI via a wireless LAN and displays it;

Fig. 107 is a flowchart showing the processing performed by a server for the example wherein the controller receives a UI via a wireless LAN and displays it;

Fig. 108 is a diagram showing an example wherein via a wireless LAN a controller receives a different UI for each user and displays it;

Fig. 109 is a flowchart showing the processing performed by a controller for the example wherein via a wireless LAN a controller receives a different UI for each user and displays it;

Fig. 110 is a flowchart showing the processing performed by a target model for the example wherein via a wireless LAN a controller receives a different UI for each user and displays it;

Fig. 111 is a flowchart showing the processing performed by a server for the example wherein via a wireless LAN a controller receives a different UI for

2025 RELEASE UNDER E.O. 14176

each user and displays it;

Fig. 112 is a table showing a UI determined in consonance with a target model and user identification information;

5 Fig. 113 is a diagram illustrating an example wherein a model in front that is to be operated performs a function that the model does not have;

Fig. 114 is a diagram illustrating an example wherein a model in front that is to be operated
10 performs a function that the model does not have;

Fig. 115 is a diagram showing an example performed when communication can not be performed directly with a model in front that is to be operated;

Fig. 116 is a flowchart showing the processing
15 performed by a controller according to a thirty-ninth embodiment;

Fig. 117 is a diagram showing an example wherein an operation/action by a user and a time are jointly stored as history along with important associated
20 information;

Fig. 118 is a flowchart for the processing performed by a controller according to a fortieth embodiment;

Fig. 119 is a flowchart for the processing
25 performed by a target model according to the fortieth embodiment;

Fig. 120 is a flowchart for the processing

2025 RELEASE UNDER E.O. 14176

performed by a server according to the fortieth embodiment;

Fig. 121 is a table showing example updated history information;

5 Fig. 122 is a diagram illustrating an example wherein an operation is performed based on history;

Fig. 123 is a diagram illustrating the example wherein the operation is performed based on history;

10 Fig. 124 is a diagram showing an example structure for a controller;

Fig. 125 is a diagram showing another example structure for a controller;

Fig. 126 is a diagram showing an additional example structure for a controller;

15 Fig. 127 is a diagram showing a functional arrangement according to a forty-second embodiment;

Fig. 128 is a flowchart showing the processing for the forty-second embodiment;

20 Figs. 129A, 129B, 129C, 129D, 129E and 129F are example task tables;

Fig. 130 is a diagram showing an example input/output apparatus that can operate another apparatus;

25 Fig. 131 is a diagram showing an example input/output apparatus that can operate a system consisting of a plurality of apparatuses;

Fig. 132 is a diagram illustrating example

2025 RELEASE UNDER E.O. 14176

input/output apparatuses that can communicate with each other;

Fig. 133 is a diagram illustrating an example input/output apparatus that can acquire information
5 from another apparatus;

Fig. 134 is a diagram illustrating an example input/output apparatus that can store information in another apparatus;

Fig. 135 is a diagram illustrating an example
10 input/output apparatus that can send an instruction to another apparatus;

Fig. 136 which is composed of Figs. 136A and 136B are flowcharts showing the processing for the task
<COMMUNICATE>;

Fig. 137 which is composed of Figs. 137A and 137B
15 are flowcharts showing the processing for the task
<PULL>;

Fig. 138 which is composed of Figs. 138A and 138B are flowcharts showing the processing for the task
20 <PUSH>;

Fig. 139 which is composed of Figs. 139A and 139B are flowcharts showing the processing for the task
<INDICATE>;

Fig. 140 which is composed of Figs. 140A and 140B
25 are flowcharts showing the processing for the task
<RESPOND>;

Fig. 141 is a flowchart showing the processing for

Sheet "E0000000"

5

5

LO

LO

15

15

15

20

20

25

25

25

25

session;

Fig. 154 is a diagram illustrating an example mail transmission;

Fig. 155 is a diagram illustrating example
5 instructions task INDICATE session;

Fig. 156 is a diagram illustrating another example instructions task INDICATE session;

Fig. 157 is a diagram illustrating additional example instructions task INDICATE session;

10 Fig. 158 is a diagram showing the flow of an operation following the operational procedures performed for another apparatus;

Fig. 159 is a diagram illustrating an example wherein a PC transmits a printing instruction to a
15 printer;

Fig. 160 is a diagram for explaining an example wherein a PC is employed as a server terminal;

Fig. 161 is a diagram for explaining an example wherein a scanner and a printer are controlled by a PC;

20 Fig. 162 is a diagram showing a relationship between a print job status change and a process associated with each status;

Fig. 163 which is composed of Figs. 163A and 163B are flowcharts showing printing processing;

25 Fig. 164 is a diagram showing a relationship between a print job and its processing, and a user's operation; and

2025 RELEASE UNDER E.O. 14176

Fig. 165 is a diagram showing an example display screen for a user for operating a print job.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

5 The preferred embodiments of the present invention will now be described while referring to the accompanying drawings.

[First Embodiment]

10 Fig. 1 is a diagram illustrating a system arrangement according to a first embodiment in which a PC (Personal Computer) 101, a scanner 102, a color printer 103 and a monochrome printer 104 are connected to a network.

15 In this embodiment, when an apparatus in a system wherein a plurality of apparatuses are connected together is instructed to execute a specific job, the apparatus analyzes the object of the job by examining its contents, and thus ascertains which job to execute. As a result of the analysis, the apparatus acquires
20 necessary information concerning the job and thereafter executes it.

25 If for the execution of a job there is available a more effective method or another and better apparatus than an instructed method or an assigned apparatus, an instruction is issued to the better apparatus or a notice is transmitted to a user to propose the use of the more effective method. Further, as a consequence

Job types are an operation input by a user, an execution of an instruction received from another apparatus, the acquisition of results by analyzing a job, or a job that is newly generated by an owned apparatus during an idling period. When, for example, a document is to be read by a scanner and printed by a printer, the following jobs are generated.

- 25 A method for generating and managing these jobs
will later be described in detail by referring to an
eleventh and following embodiments.

25 A method for generating and managing these jobs
will later be described in detail by referring to an
eleventh and following embodiments.

The procedures according to which a plurality of apparatuses execute the above described processes will be specifically described while referring to the drawings.

5 Fig. 2 is a diagram illustrating the functional arrangement for performing the processing in this embodiment. A job reception unit 201 receives a job from a user or another apparatus. The received job is registered in a job table. A job analysis unit 203
10 reads and analyses a job registered in the job table 202. Another apparatus information acquisition unit 204 acquires the attributes and the current states of the other apparatuses that are connected. A state determination unit 207 determines the state from the
15 current states of the other apparatuses.

 An optimum planning unit 206 makes an optimal plan for the execution of a job. A job execution determination unit 207 determines whether a job should be executed, or when the job is to be executed, and
20 determines whether an owned apparatus or another apparatus will execute the job. When another apparatus executes the job, another apparatus instruction unit 208 sends an instruction to another apparatus for the job execution. When the owned apparatus executes the
25 job, a job execution unit 209 executes the job. An execution notification unit 210 notifies a user that the execution instruction has been issued to another

apparatus.

Fig. 3 is a diagram showing the hardware arrangement of the units that perform the processing in this embodiment.

5 An I/O 301 exchanges input/output data with external apparatuses. A CPU 302 executes a program and controls the individual units. A ROM 303 is used to store programs, which correspond to individual flowcharts that will be described later and which are
10 to be executed by the CPU 302, and fixed data. A RAM 304 is used to temporarily store variables and intermediate data, such as the attributes and the current states of the other apparatuses acquired by the other apparatus information acquisition unit 204, that
15 are generated during the processing. A program from an external source may be loaded into the RAM 304 and stored therein.

Fig. 4 is a flowchart showing the processing performed for the first embodiment.

20 At step S109, the contents of the job table are initialized. At step S110, in order to determine whether a job has been input, a check is performed to determine whether or not a job has been input by a user, a job has been input by a device that can be
25 detected by the system, from results obtained by analyzing the job, or a new job has been generated by an owned apparatus during idling. When a job has been

input, at step S111, the input job is added to the job
table. At step S112, the job table is examined to
determine whether there is job. If there is a job, at
step S113 the job is extracted. At step S114 a
5 received instruction is analyzed, and from the
information thus obtained, the object of the job is
acquired. At step S115, the analyzed instruction is
employed to search for a job that is to be executed.
At step S116 a job that is searched for at S115 is
10 registered.

At step S117 a check is performed to determine
whether or not there is a job that has not yet been
executed. If there is such a job, program control
advances to step S118. At step S118 a check is
15 performed to determine whether or not the job can be
executed. When it is ascertained that the job can not
be executed, program control returns to step S115 and a
job that must be executed is searched for. At step
S119 the job is executed and program control returns
20 thereafter to step S117.

If a user sends an instruction, for example, to
read a document using a scanner and to print the
document using a printer, it is assumed that, as a
result of the analysis, the acquisition of a printed
25 document is the object of a user. In this case, a
document reading and analysis process, which is
generated by analyzing information received by the

2025 RELEASE UNDER E.O. 14176

scanner from the user, and a process for instructing a printer to print the document that has been read are searched for as jobs. These processes will be described in detail during the course of the eleventh and the following embodiments while referring to specific examples.

Fig. 5 is a diagram showing a process for selecting from among a plurality of printers an optimal printer for performing printing.

In Fig. 5, job information is input/transmitted as a command from a host computer or an instruction from a remote controller, or is obtained by analyzing a voice command issued by a user using natural language, or from bar code or a sentence read from a cover page.

A device that has received the job information analyzes the job, and then selects a printer that can execute a process suitable for the job and outputs the data to the printer. Further, when there is an instruction for notification, the device selects an optimal medium and dispatches a notice thereto.

Therefore, upon the receipt of a request from a user, the structure of the printer is referred to, and an appropriate printer is selected to perform the printing. At this time, in consonance with the situation, the processing can be allocated for a plurality of printers. Further, when there is an instruction for notification, an optimal medium is

selected to dispatch a notification that the printing has been terminated along with the name of the printer that has performed the printing.

A request submitted by a user concerns paper sizes, printing quality, colors and time limit (e.g., completion of printing by 5 o'clock). The printer configuration covers the printer types and the number of printers in the system, and their performances or their current statuses (whether the printers are normally operated, whether there is a printing queue, or whether paper or toner is insufficient). As for a medium and a method used for notification, a notification is transmitted by voice through a user's terminal or by telephone, or a notification message is transmitted to a pager, or a document describing the contents of a notification is transmitted by electronic mail or by facsimile.

A situation where the individual units perform the processing shown in Fig. 5 will now be described while referring to the flowchart in Fig. 4.

First, if, at step S110, an urgent instruction for outputting a specific document by five o'clock is transmitted to a host computer, at step S111 a job is added to a job table. At step S113, the job is extracted from the job table and at step S114 the received instruction is analyzed to obtain the object of the job.

At step S115, the following jobs are searched for following the analysis of the instruction.

- (1) Acquisition of specifications (paper size, printing quality, color document, etc.) to be used for selecting a suitable printer for outputting a document, and of other information, such as time limit.
- (2) Selection from among the connected printers of a suitable printer for specifications (1).
- (3) Examination of the selected printer to determine whether or not any obstacle to printing output exists.
- (4) Output data to a selected printer.
- (5) Issuance of the selected printer and a notification that the data has been output.

At step S116, the job found at step S115 is registered. The above process is repeated until, at step S117, there are no jobs to be searched for. At step S118 a check is instituted to determine whether or not the job can be performed. When the performance of the job is not possible, another job that must be executed is searched for. At S119, the jobs that have been searched for are sequentially performed.

[Second Embodiment]

Fig. 6 is a diagram for explaining an example wherein a remote controller (hereinafter referred to merely as a controller) is employed as a means for sending instructions to various devices.

5

10

[Third Embodiment]

15

20

2.5

a color printer 704 if color printing is requested);

(3) data for a document having a large number of pages are allocated to a plurality of printers to print; or

(4) if a transfer destination is designated at the

5 addressee, the data is transferred to the transfer destination.

[Fourth Embodiment]

Fig. 8 is a diagram showing an example where a document is read by a scanner and is transmitted to a specific printer that the scanner can not manage because it is in a different network domain, etc.

When, a document is read by a scanner 701 in Austin, a user designates an addressee by voice, etc., or an addressee that is described using a character string or a bar code on a cover sheet is read and recognized/interpreted to determine the addressee. As a result, a monochrome printer 702 in Tokyo is determined to be the addressee. After the document data are transmitted to the monochrome printer 702:

20 (1) when the monochrome printer 702 is not ready for printing, it transmits the data to another printer (a monochrome printer 703) for printing;

(2) if the monochrome printer 702 is not ready for printing the received document data because of specified conditions, such as color and paper size, it transmits either all the data for the received document or only data for pertinent pages to another printer

2025 RELEASE UNDER E.O. 14176

(e.g., a color printer 704, if color printing is requested);

(3) if a document has a large number of pages, the monochrome printer 702 prints part of the data and also
5 allocates printing data to a plurality of other printers; or

(4) if a transfer destination is designated at the monochrome printer 702, the printer 702 transfers the data to the transfer destination.

10 A difference between the third and the fourth embodiments is that in the third embodiment the scanner 701 determines the addressee, and in the fourth embodiment the printer 702 that received the document from the scanner 701 determines the transfer
15 destination.

[Fifth Embodiment]

Fig. 9 is a diagram showing an example wherein a document is read by a scanner and is transmitted to a specific printer that the scanner can not manage
20 because it is in a different network domain, etc.

When, a document is read by a scanner 701 in Austin, a user designates an addressee by voice or using a keyboard, or an addressee that is described using a character string or a bar code on a cover sheet
25 is read and recognized/interpreted to determine the addressee. As a result, a monochrome printer 702 in Tokyo is determined as the addressee. After document

data are transmitted to the monochrome printer 702, they are further transferred to a personal computer 705 that can perform a higher level operation.

As a result, the personal computer 705 determines, from the entry "urgent" on the cover letter, for example, that the document is an urgent document. The personal computer 705 examines schedule data to find the location of the recipient of the document, and transfers the data to that location, for example, Atsugi. At this time, if the transfer destination is not a printer but is a different medium, such as a facsimile machine 706, medium conversion is performed before transmission.

[Sixth Embodiment]

Fig. 10 is a diagram showing an example wherein a document is read by a scanner and is transmitted to a specific printer that the scanner can not manage because it is in a different network domain, etc.

When, a document is read by a scanner 701 in Austin, a user designates an addressee by voice, etc., or an addressee that is described using a character string or a bar code on a cover sheet is read and recognized/interpreted to determine the addressee. As a result, a monochrome printer 702 in Tokyo is determined as the addressee. After document data are transmitted to the monochrome printer 702, they are further transferred to a personal computer 705 that can

5 [Seventh Embodiment]

When a PC 1102 acquires the status of a printer
10 1103 across a network and detects a change in the
status, such as the occurrence of an error or an event,
the PC 1102 determines a notification destination, such
as a user or a manager, in consonance with the contents
of the change, and employs a medium corresponding to
15 the determined destination to transmit a notification.
For example, to transmit a notification to a terminal
1101 of a user or a manager, the PC 1102 uses
electronic mail, or a telephone 1104, or transmits a
message to a pager 1105.

20 Therefore, in the example in Fig. 10, for example,
a notification of the reception of the document may be
issued using electronic mail or a pager, instead of the
telephone 707.

[Eighth Embodiment]

25 In this embodiment, before executing an instructed
job an apparatus notifies a user of the contents of the
job in accordance with the type or the condition of the

job, or cancels a job that is determined to be unnecessary for a user.

Fig. 12 is a flowchart showing the processing in this embodiment. Fig. 13 is a table showing, in
5 consonance with the types and conditions of jobs, whether or not an advance notice should be issued.

In Fig. 12, first, at step S120 a check is performed to determine whether or not a job constitutes necessary information for a user. If this is true, the
10 processes at step S122 and the following steps are performed. If not, at step S127 the job is canceled. At step S122, information concerning the advance notice that corresponds to the job type and conditions in Fig. 13 is referred to, or the contents described on a cover
15 sheet are analyzed to determine whether or not a notice for the process to be executed and the contents of the process should be issued to a user prior to the performance of the instructed job. When advance notice is not required, program control moves to step S126.
20 When advance notice is issued, program control moves to step S124, whereat a user is notified of the process to be performed and its contents. At step S125, the permission for the performance is received from a user, if necessary. At step S126 the job is performed.

25 An explanation will be given for an example wherein, when the contents of a job call for the filing of information, an analysis of the system contents is

performed prior to the filing of information, and information concerning the contents is transmitted to a user.

Fig. 14A is a diagram showing an example wherein
5 filing process information to be filed is transmitted to a user in advance. A file storage unit 1401, a scanner 1402 and a user terminal 1403 are provided in this system. The processing performed by the scanner 1402 in Fig. 14A will now be described while referring
10 to the flowchart in Fig. 12.

At step S120, since an instructed job is for information filing, it is assumed that this is necessary for a user. At step S122, while information designated in Fig. 13 is referred to, it is ascertained
15 that a notice concerning information to be filed should be issued before the filing, and that the information should then be scanned. Program control then moves to step S124 to issue a notice concerning information to be filed. At step S124 the scanned information is
20 transmitted to the user terminal 1403 via a network. At step S126, the filing job is performed.

Next, an explanation will be given for an example wherein the information on the first page is received and analyzed, and when the information is not at all
25 related to a user, the following information is not received.

Fig. 14B is a diagram showing an example wherein

2025 RELEASE UNDER E.O. 14176

whether or not a large amount of data to be received is required by a user is determined by examining the first page, and the receipt of information for the following pages is canceled. A reception PC 1404 and a
5 transmission PC 1405 are provided.

The processing performed by the PC 1404 in Fig. 14B will be explained while referring to the flowchart in Fig. 12.

At step S120, the first page of the received data
10 is analyzed. Since "For All Persons In Charge Of General Affairs Information" is entered on the first page, it is apparent that this document is not intended for a user who is not in charge of general affairs information, and the receipt of the information is
15 determined to be unnecessary. Program control therefore moves to step S127. At step S127, the first page, which has been received, is canceled, and information for the second and the following pages is not received. The processing is thereafter terminated.
20 [Ninth Embodiment]

Fig. 15 is a flowchart showing the processing for a ninth embodiment. In this embodiment, an apparatus that is designated to perform the processing determines whether it or another apparatus should perform the
25 processing, and as a result of the determination, either performs the processing itself or sends an instruction to another apparatus to perform the

processing.

At step S150 a check is performed to determine whether or not a job has been input. If a job has been input, at step S151 the input job is entered in a job
5 table. At step S152 the job table is examined to determine whether any jobs have been entered. If they have been, at step S153 a job is extracted from the table. At step S154 a received instruction is analyzed and the object of the job is apprehended using the
10 result. At step S155 the status of the apparatus is examined. At step S156 the status of another apparatus consonant with the object of the job is examined.

When, as the result of a comparison of the statuses of the locally owned apparatus and other apparatuses,
15 it is found that the locally owned apparatus is optimal for the performance of the job, program control moves from step S157 to step S158, whereat it is determined that the owned apparatus will perform the job, and at step S159 the job is performed by the locally owned
20 apparatus. If there is an optimal apparatus other than the locally owned apparatus that has capabilities consonant with the object of the job, program control goes from step S160 to step S161, whereat it is determined that the other apparatus will perform the
25 job, and at step S162 the locally owned apparatus sends a job execution instruction to the apparatus having capabilities consonant with the object of the job. At

step S163 the locally owned apparatus notifies a user that another apparatus has executed the job.

If there is no apparatus having capabilities consonant with the object of the job, program control
5 moves from step S160 to step S164, whereat a plan is prepared for the use of an optimal method that does not depart from the object of the job, and at step S165 the plan is proposed to a user.

Fig. 16A is a diagram showing the transmission of
10 information in this embodiment.

When a user of a PC 101 provides for a printer 104 a job for the output of information input by a scanner 102, and when the printer 104 has, for example, a printing malfunction, the printer ascertains that it
15 can not perform the instructed job, and by communicating with other apparatuses, it finds a printer 103 that can perform the instructed job. Thus, the printer 104 determines that the printer 103 can act for it and perform the job, and so instructs the
20 printer 103. Further, the printer 104 transmits a notification to the PC 101 to inform the user of the action that it took. In Fig. 16A, the process flow for these activities is described by arrows.

The processes performed by the individual units in
25 Fig. 16A will be described while referring to the flowchart in Fig. 15.

First, the process performed by the scanner 102

2025 RELEASE UNDER E.O. 14176

will be explained. At step S150 the scanner 102 scans a document and acquires a job, information concerning which is to be transmitted to the printer 104. At step S151 this job is entered in the job table, and at step 5 S153 the job is extracted. At step S154, the scanner 102 scans additional data and determines that the data is a job to be transmitted. At step S155, the scanner 102 ascertains that it is operating normally and that no problem exists in the scanning and transmission of 10 instructed information.

At step S156 it is ascertained that the job can not be transmitted to another apparatus. At step S157, since optimally the scanner 102 should execute the job, program control moves to step S158. At step S158 the 15 scanner 102 determines that it should scan the information, and at step S159 the scanner 102 scans the information and transmits it to the printer 104 via a route 1 on a network.

At step S150, the printer 104 receives the job for 20 the output of received information. At step S151, the printer 104 enters the job in the job table, and at step S153, it extracts it. At step S154, the printer 104 ascertains from the information it receives that the information for the user from the PC 101 is to be 25 printed on paper. At step S155 the printer 104 determines that it is out of toner and disables printing. At step S116 the printer 104 searches, via

2025 RELEASE UNDER E.O. 14176

the network, for printers that can output the received information, and finds the printer 103 (route 2).

Since, at step S157, the printer 104 can not execute the job, program control moves to step S160.

5 Then, as at step S160 it is determined that the job for the output of information can be performed by the printer 103, at step S161 it is determined that the received information should be transmitted to the printer 103. At step S162 the printer 104 sends an
10 instruction to the printer 103 to print the information that is to be received (route 3). At step S163 to notify the user that the instructed job was performed by the printer 103 electronic mail for the user is transmitted to the PC 101 (route 4).

15 Fig. 16B is a diagram showing the transmission of information for a case where no apparatus having capabilities consonant with the object of a job is available.

When the user of the PC 101 provides a job for the
20 output to the printer 104 of information input by the scanner 102, and when the printer 104 disables printing because it is out of toner, the printer 104 communicates with other apparatuses, finds the printer 103, which is suitable for the object of the job, and
25 determines its status. Then, since the printer 103 disables printing because it is out of paper, and as there is no other printer available that is suitable

for the object of the job, a notice is issued to the PC 101 to propose to the user an optimal plan whereby when either the printer 103 or 104 has recovered to the printing enabled state, that printer will perform the job. In Fig. 16B, the process flow for these actions is indicated by arrows.

The procedures performed by the individual units in Fig. 16B will be explained while referring to the flowchart in Fig. 15.

The process whereby the scanner 102 reads a document and transmits it to the printer 104 is performed in the same manner as was described previously.

At step S150 the printer 104 receives a job for the output of received information. At step S151, the job is entered in the job table, and at step S153, it is extracted. At step S154, the printer 104 ascertains from the information it receives that the information for the user from the PC 101 is to be printed on paper. At step S155, the printer 104 ascertains that it is out of toner and printing is disabled. At step S156, the printer 104 communicates across the network with other printers to find one that can print the received information. The printer 104 determines that the printer 103 has also disabled printing because it is out of paper, and that no other appropriate apparatus is available.

Since, at step S157, the printer 104 disables the performance of the job, program control moves to step S160. At step S160, as there is no apparatus that can perform the job for the output of information, program control goes to step S164. At step S164, planning is begun to prepare an optimal method for performing the printing, which is the object of the job for the output of information. As a result, it is determined that the optimal method involves the return of a printing apparatus to its normal operating status. At step S165, the proposed method, whereby either the printer 104, which is out of toner, or the printer 103, which is out of paper, is to be recovered to the printing enabled state, is presented in a window shown in Fig. 17 for approval by the user.

Then, a response received from the user, or a change in the printer status is identified as an input job, and the same processing is again performed. In this fashion, the object of the user can be achieved.

The above described planning will be described later in detail during the course of the explanation of specific examples for an eleventh and subsequent embodiments.

[Tenth Embodiment]

In the processing for the ninth embodiment, wherein, at steps S158 and S159, a locally owned apparatus determines to perform a job itself, and

performs the job, before another instructed job is performed, the possibility of the occurrence of a problem is analyzed in detail, as in the procedures in Fig. 17. When it is ascertained, in consonance with
5 environmental conditions or the status of the job performance, that performing the job is not advisable, a notice concerning the problem may be issued, or the request for the performance of the job may be rejected.

When, for example, an instruction for printing a
10 secret document is issued and a user is not identified as an authorized user, the instruction is rejected.

Fig. 18 is a flowchart showing the detailed procedures for the performance of a job.

At step S180 a check is performed to determine
15 whether or not a problem exists concerning the performance of the instructed job. At step S181 no problem affecting the performance of a job is found, at step S185 the job is performed. If a problem is found, at step S182 a check is performed to determine whether
20 a notice concerning the problem that was discovered should be transmitted to a user, or whether the request for the performance of the job should be rejected. When it is ascertained that such a notice should be transmitted to a user, at step S184 the notice is
25 transmitted to the user. When it is determined that the request for the performance of the job is to be rejected, at step S186 the request for the performance

SECRET E05650

of the job is rejected and a notice of rejection is transmitted to the user.

An example wherein a user of the PC 101 issues an instruction to output to the printer 104 confidential
5 information read by the scanner 102 will now be described while referring to Figs. 15 and 18. Fig. 19 is a diagram showing example confidential information to be read.

First, at step S150 the scanner 102 scans
10 available information and receives a job for the transmission of information to the printer 104. At step S151 the job is entered in the job table, and at step S153, the job is extracted therefrom. At step S154 data are scanned, and it is ascertained the data
15 constitute a job to be transmitted. At step S155, the scanner 102 determines that it is operating normally and that there is no problem affecting the scanning and transmission of the instructed information.

At step S155 it is ascertained that the job can
20 not be transmitted to another apparatus. Since, at step S157, it is ascertained that optimally the scanner 102 should perform the job itself, program control moves to step S158, whereat the scanner 102 determines that it should scan the information itself.

25 At step S180, as a result of the scanning of the information, it is determined to be confidential information whose output is inhibited. Since a problem

affecting the performance of the job exists, at step S182 it is determined that the job (the scanning and the outputting of information) should be rejected. At step S183 the job is rejected, and program control
5 thereafter goes to step S186. At step S186, a notice is issued that the job was rejected.

Similarly, when a plurality of users employ the same system, the current user can be identified by a log-in name, and an instruction for the output of the
10 contents of files belonging to other users can be rejected. When, instead of an instruction from a user, a document is received from the outside and the destination user differs from the current user, the output of the received document and the notice of the
15 receipt of the document are rejected, or the processing is halted until the destination user begins to employ the system.

[Eleventh Embodiment]

The processing for an eleventh embodiment will now
20 be described while referring to Fig. 4. At step S109 the job table is initialized. Then, at step S110 a check is performed to determine whether there is input from a user or from an apparatus that can be detected by the system. At step S111 an input analysis job is
25 entered in the job table to analyze the contents input at step S110. At step S112 a check is performed to determine whether there is a job to be performed. If

there is such a job, it can be acquired at step S113. At step S114, the object comprising the background for the performance of the job is understood.

At step S115 a possible process is planned by
5 using the contents that are input, the status of a device that can be detected by the system, and the knowledge that the system has currently acquired. At step S116 a new job is added if necessary. At steps S117 to S119 the process as planned at step S115 is
10 performed in consonance with the contents. The processing is repeated until no more jobs remain, and program control thereafter returns to step S110.

A case where a user is to print <file A> will now be explained. Fig. 23 is a diagram showing the
15 contents of <file A>, the colored picture of a car. Fig. 1 is a diagram showing the structure of the system in this embodiment. A user sends an instruction from a PC 101, and a monochrome printer 104 is set as a normally used printer. A color printer 103 is also
20 set.

At step S109 the job table is initialized. At step S111 a job that is to be performed when there is no input is added to the job table (Fig. 20). When file name <file A> is designated in a window in Fig. 21
25 and printing for it is selected, at step S110 it is determined that there is input, and program control advances to step S111. At step S111, as is shown in

5

10

15

25

a job when there is no response from a user is to

determine whether a proposal can be accepted. At step S115 it is determined from the flow condition and the status that the user should be queried by telephone.

* The telephone number of the current location of the user is acquired (schedule data in Fig. 26)

* The printing priority is urgent (according to the schedule data in Fig. 26, file A is to be used at the business talk at 13:00).

At step S119 a query, "Perform printing with a color printer?" is directed to the user (Fig. 27). At the same time, a job corresponding to an event is added to the job table when no response is received from the user (Fig. 28). Program control thereafter returns to step S110.

When, at step S110, a user responds with "Yes, please" as is shown in Fig. 27, it is assumed that data input is to be performed, and program control moves to step S111. At step S111 an input analysis job is added to the job table (Fig. 21). At step S112 it is assumed that there is a job to be performed, and program control moves to step S113. At step S113, a job to be performed, the input, "Yes, please" is analyzed. At step S114 it is ascertained that the object of the input, "Yes, please" is the acceptance of the proposal.

At step S115 it is determined that <file A> is to be transmitted to and printed by the color printer 103. At step S118 <file A> is transmitted to and printed by

2025 RELEASE UNDER E.O. 14176

the color printer 103. At the same time, a job for confirming whether or not the printing has been terminated normally is added to the job table (Fig. 29). Program control thereafter returns to step S110.

5 If, at step S110 there is no data input and at step S112, as is shown in Fig. 30, the printer status is changed from "Printing" to "Printed document in tray" it is assumed that there is a job to be executed, and program control advances to step S113. At step
10 S113 a process corresponding to the job to be executed, printer status, is acquired. At step S114, from a printer status entry in Fig. 31, the status "Printed document in tray" means that there is a printed document in a printer tray, and the object of the job
15 is understood to be the delivery of the printed document to a user.

 At step S115, a waiting state is specified because the user may soon come to pick up the printed document. At step S116, a job for confirming whether the user has
20 come and has picked up the printed document is added to the job table (Fig. 32). Program control thereafter returns to step S110. If, at step S110, there is no input for ten minutes and at step S112 the printed document is still on tray, there is a job to be
25 executed, and program control therefore advances to step S113. At step S113 a process corresponding to the job to be executed, when the printed document is still

2025 RELEASE UNDER E.O. 14176

on hand, is acquired. At step S114, from the table in Fig. 31 the status "Printed document on tray" means that a printed document is still in the printer tray, and it is assumed that the object is the delivery of the printed document to the user. Since at step S115 the printed document has not been picked up for ten minutes, it is assumed that the user has forgotten to collect the document, and it is determined that a notice, "Printed document is in color printer tray" is to be issued (Fig. 33). Also, a job corresponding to the failure of the user to respond and a job corresponding to the collection of the printed document by the user are added to the job table (Fig. 34). Program control thereafter returns to step S110.

When at step S110 there is no input and at step S112 the printer status is changed from "Printed document in tray" to "Normal" as is shown in Fig. 28, there is a job to be executed and program control advances to step S113. At step S113 a job corresponding to the job to be executed, printed document in tray, is re-evaluated. At step S114 the object for the rechecking of the job corresponding to the "Printed document in tray" is understood to be the deletion of an unnecessary job. At step S115, it is determined that the job of waiting for a response from the user should be deleted, and at step S119 the job of waiting for the user's response is deleted. A new job

is not added. While the job table is in its initial state, program control returns to step S110.

Figs. 36 and 37 are tables showing plans, actions and rules.

5 When a user presses the button "Print" in the printing window in Fig. 21, it is determined by referring to the plans and actions in Fig. 36 that the object of the user is the changing of the current state to the "Printed document in tray". In addition, since
10 "Printed document in tray" is the assumption for the object "Acquire printed document" the final object of the user is determined to be "Acquire printed document".

 When a user expresses agreement or disagreement by
15 voice or by the manipulation of the mouse in response to the query in the inquiry window in Fig. 24 or the window in Fig. 33, or the telephone query in Fig. 27, it is determined that the object of the user is the statement of the agreement or disagreement relative to
20 the query.

 In Fig. 37 the final object of the system is the thus constitutes the achievement of the object of the user. As the basis for this, the system must be stable. In addition, the system must (1) apprehend the
25 object of the user and (2) must make a plan for the achievement of the object and execute it.

 To stabilize the system, not only an abnormal

SECRET

timing for the system must be adjusted to the normal condition, but also the system must be powered off when it is not required in order to reduce costs and to prevent the system from becoming unstable.

5 Fig. 38 is a diagram that for easier understanding shows only one part of the table in Fig. 37.

 In order to understand the object of the user, data that is input is identified. Further, corresponding to "acquire printed document" which is
10 the object of the user in Fig. 36, "Transfer printed document to user" which is the object of the system.

 The presence of a printed document is the premise for the transfer of the printed document to a user, and the object is achieved by notifying the user of the
15 location of the document. Of course, the user must collect the document or the document must be delivered to the user by some means in order for the user to acquire the document; in this embodiment, it is
20 determined that when the printed document is no longer in the printer tray, that is the equivalent of the user having acquired the document.

 The presence of an original document and the printing conditions are required in order to obtain a printed document, and it is premised that a
25 corresponding printing environment normally exists. In this situation, a corresponding printing environment is selected to perform printing. The original document

must be so prepared that its existence is constant. In addition, to clarify the printing conditions, only when there is a question concerning a condition need ask a user queries. When a printing environment is abnormal, the printing environment is normalized to maintain normal environment. When no response is received from a user within a predetermined period of time, additional planning must be performed to ascertain the intent of the user.

10 The properties of each device are stored in a memory in each device, or in the memory of the server that manages each device. Fig. 39 is a table showing the properties of the devices. The statuses of the devices are held in the devices, and are voluntarily transmitted to other apparatuses by the devices, or by 15 the passive transfer of them when requested by another server.

 In this system, the properties are inherent to the individual devices and do not change; they are acquired 20 when the system is activated or when a connection across the network is altered. In the planning process, the statuses are acquired, as needed, or at a specific time interval, and are updated as information intended for the internal memory.

25 [Twelfth Embodiment]

 An explanation will now be given for the processing performed in a case where, as in the

20250727 14:56:56

eleventh embodiment, a color printer is busy when <file A> is to be printed.

First, when "Print <file A>" is input, it is entered in the job table, and its object is understood to be a request that printing be performed. Assume as the condition/situation that the colored portion is included in a document and a color printer is busy. A plan is devised to query a user concerning whether the job can wait until the color printer is not busy, or whether the data can be printed in monochrome. The query, "The color printer is busy. Wait, or print in monochrome?" is presented to a user. When the user selects "Wait" the process is placed on standby until the color printer is no longer busy.

[Thirteenth Embodiment]

When "<file A> was changed to <file A'>" is input, it is ascertained that the updating of the job table is the object. As the condition/situation, the <file A> printing job is stored in the job table. Thus, a plan is made to query a user concerning the changing of the printing target to <file A'>. Then, the query "Print <file A'> instead of <file A> before amended?" is presented to the user.

[Fourteenth Embodiment]

According to this embodiment, in a system wherein a plurality of apparatuses are connected together (in this case, they are connected across a network), when a

job for an individual apparatus is instructed, an analysis of the object of the job is performed by the appearance. When the apparatuses determine from their statuses and the status of the instructed apparatus,
5 that the instructed apparatus should not execute the job, the performance of the job is transferred to another apparatus.

Figs. 41A and 41B are diagrams in each of which is shown the condition where a plurality of apparatus are
10 connected to a network. A network in Fig. 41A provides an environment wherein a scanner 411 and printers 412 and 413 can determine the states of the other apparatuses. A network in Fig. 41B provides an environment wherein the scanner 411 and the printers
15 412 and 413 can not determine the states of the other apparatuses.

Fig. 42 is a diagram illustrating a functional arrangement for performing the processing in this embodiment. A job reception unit 421 receives a job
20 from a user or from another apparatus. A received job is registered in a job table 422. A job analysis unit 423 extracts the job from the job table 422 and analyzes it. Another apparatus information acquisition unit 424 determines the attributes and the current
25 statuses of other connected apparatuses. A self state determination unit 427 determines the attribute and the current state of the self apparatus.

An optimum planning unit 425 prepares an optimal plan for the performance of a job. A job performance determination unit 428 determines whether or not a job is to be performed, and whether the locally owned apparatus or another apparatus should perform the job. When the job is to be performed by the locally owned apparatus, a job performance unit 426 performs it. When another apparatus is to perform the job, another apparatus job transfer unit 429 transfers the job to another apparatus. A transfer notification unit 430 notifies a user of the results obtained by the job performance or the transfer of the job to another apparatus. Fig. 43 is a main flowchart showing the processing performed for this embodiment.

At step S430, in order to determine whether a job has been input, a check is performed to determine whether or not a job has been input by a user, a job has been input by a device that can be detected by a system, based on the results obtained by analyzation of the jobs, or a new job that has been generated by the locally owned apparatus while idling. When a job has been input, at step S431, an input job is added to the job table. At step S432, the job table is examined to determine whether there is a job. If there is a job, at step S433 the job is extracted. At step S434 a received instruction is analyzed, and from the information attained by the analyzation, the object of

the job is obtained. At step S435 a check is performed to determine whether or not a job for another apparatus is present. If there is such a job, at step S436 control of another apparatus is initiated. If there is
5 no such job, at step S437 a control process the locally owned apparatus is initiated.

Fig. 44 is a flowchart for the process for controlling another apparatus performed at step S436 in the main flowchart.

10 At step S440 the status of an apparatus that is designated in the job is examined, and at step S441, based on the status, a check is performed to determine whether a problem affecting the performance of the job by the designated apparatus exists. If no such problem
15 exists, at step S442 the job is transmitted to the designated apparatus. If a problem affecting the performance of the job by the designated apparatus exists, at step S443 a check is performed to determine whether or not there is an apparatus other than the
20 designated apparatus that is suitable for the performance of the job. If there is such an apparatus, its status is examined. As a result, if there is another apparatus that can execute the job, at step S445 the job is transferred to that apparatus, and at
25 step S446 the user is notified of that the job was transferred to that apparatus. When there is no apparatus other than the designated apparatus that can

perform the job, or when another suitable apparatus can not be used at that time, at step S447 an optimal plan is devised that will not degrade the object of the job, and at step S448, the plan is proposed to the user.

5 Fig. 45 is a flowchart for the process for controlling the locally owned apparatus performed at step S437 in the main flowchart.

At step S450 the status of the locally owned apparatus is examined, and at step S451, based on the
10 status, a check is performed to determine whether a problem affecting the performance of the job by the locally owned apparatus exists. If no such problem exists, at step S452 the job is performed by the locally owned apparatus. If a problem affecting the
15 performance of the job by the locally owned apparatus exists, at step S453 a check is performed to determine whether or not there is an apparatus other than the locally owned apparatus that is suitable for the performance of the job. If there is such an apparatus,
20 its status is examined. As a result, if there is another apparatus that can execute the job, at step S455 the job is transferred to that apparatus, and at step S456 the user is notified that the job was transferred to that apparatus. When there is no
25 apparatus other than the locally owned apparatus that can perform the job, or when another suitable apparatus can not be used at that time, at step S457 an optimal

plan is devised that will not degrade the object of the job, and at step S458, the plan is proposed to the user.

Fig. 46 is a diagram showing the condition that exists when, while, in Fig. 41A, an instruction is issued to output to the printer 412 along route A information that has been read by the scanner 411, the other apparatus information acquisition unit 424 of the scanner 411 discovers a malfunction at the printer 412, and this information is output to the printer 413 along route B.

Fig. 47 is a diagram showing the condition that exists when, while, in Fig. 41B, the scanner 411 is instructed to output the information that is read to the printer 412 along route A and to confirm the status of the printer 412, since the printer 412 is located in a remote area, the scanner 411 takes the status of the network into account and unconditionally transmits the information to the printer 412, which then, because a malfunction has occurred there, transfers the received information (job) to the printer 413.

The processing performed in Figs. 46 and 47 will be described while referring to the flowcharts shown in Figs. 43 to 45.

When in Fig. 46 a job is to be output by the scanner 411 and transferred to the printer 412, the scanner 411 performs the following process.

First, at step S430 the scanner 411 receives a job for the scanning of information and the transmission of it to the printer 412. At step S431 the job is entered in the job table, and at step S433, it is extracted
5 therefrom. At step S434 the scanner 411 scans the data and ascertains the job involves the transmission of data to a designated printer. At step S435 it is determined that there is a job, which is to be executed by another apparatus, for the output of the scanned
10 information by the printer 412. Based on this determination, at step S436 program control moves to another apparatus control process in Fig. 44.

At step S440 the current state of the printer 412 is acquired. Then, information that the printer 412
15 has malfunctioned is received, and at step S441 it is determined that printing by the printer 412 is disabled. In this case, besides a malfunction, the printer 412 can also be in an out of paper or out of toner disabled state. At step S443, it is assumed that
20 the designated printer 412 can not execute the job, and another apparatus that can execute the job is searched for by communicating with the other apparatuses across the network. At step S444 it is found that the printer 413 can execute the job and the performance of the job
25 is assigned to it.

At step S445 the scanned information is transmitted to the printer 413. And at step S446,

since a process other than the one instructed is being performed, the user is notified of the job alteration. Since the process for the instructed job has been terminated, the system waits for the next job.

5 Following this, a process in Fig. 47 where a job is to be output by the scanner 411 and transmitted to the printer 412 will now be explained.

10 First, at step S430 the scanner 411 receives a job for the scanning of information and the transmission of the information to the printer 412. At step S431 the job is entered in the job table, and at step S433, it is extracted therefrom. At step S434 the scanner 411 scans the data and ascertains the job is for the transmission of data to a designated printer. At step
15 S435 it is determined that there is a job, which is to be executed by another apparatus, for the output of the scanned information by the printer 412. Based on this determination, at step S436 program control moves to another apparatus control process in Fig. 44.

20 At step S440, while the scanner 411 communicates with the printer 412 and attempts to acquire its status, it is found that the printer 412 is in a remote area and the scanner 411 decides to transmit the information, regardless of the status of the printer
25 412. At step S441 it is determined that there is no problem with the printer 412 since it is in a remote area, and at step S442 the scanned information is

At step S430 the printer 412 receives the job for outputting the received information. At step S431 the job is entered in the job table, and at step S433, it is extracted therefrom. At step S434 the printer 412 understands that the job is for the printer 412 to output the received information. At step S435 it is determined that there is no job for another apparatus, and at step S437 program control moves to an own apparatus control process in Fig. 45.

At step S454 the printer 413 that can execute the job is found, and the execution of the job at the printer 413 is determined. At step S455, the printer 412 transmits the received information to the printer 413. At step S456, since the process other than being

instructed is performed, the user is notified of the alteration of the job. In this embodiment, such a notice is issued to the instruction source user. Since the output destination is far away from the instruction source, the notice may be issued to a recipient. Since the instructed job has been terminated, the system waits for the next job. As at the printer 413 there is no processing problem and the printer 413 can perform the job for the output of the received information, the printer 413 performs the job.

In the above embodiment, the individual units automatically transfer the job. If there is a problem at each apparatus, a user may provide a transmission order for the transfer of the job by the apparatuses. In this embodiment, a user inputs as a job the employment of a designated printer to print a scanned document; however, a second and a third printer may at the same time be set for the job, so that if the designated printer malfunctions they can replace it and perform the printing. Thus, at step S443 or S453, the second or the third printer can be selected as a suitable apparatus for the job and its status is examined. A second or a third printer may be set as a printer to receive a job and to replace a designated printer when it is in a printing disabled state. However, even when a second or the third printer is not set for the job, the printer that receives the job can

transfer it in consonance with destinations that are set internally.

In addition to a malfunction and an operation disabled state, the following conditions can cause the performance of a job to be canceled: the specifications may be inappropriate for the performance of the job, e.g., a case where a job for the printing of color data is issued to a monochrome printer; or immediate processing of the job may not be possible because there are too many jobs in a queue.

[Fifteenth Embodiment]

In this embodiment, in a process for determining the status of the locally owned apparatus at step S450 in Fig. 45, schedule information for a user, which is the object, is examined as a factor that is used to determine whether a problem exists that will affect the performance of a job involving the output to a user of urgent information received by a printer.

An explanation will be given for a process that is to be performed in the environment shown in Fig. 48, where a user, to whom urgent information is to be transmitted, is currently at an outside location at which a printer 412 is available that is connected to a network.

In the procedures in Fig. 43, at step S434 it is ascertained that the object of the job is the transmission to a user of urgent information that has

been received. At step S435, since at this time there is no job for another apparatus, program control moves to step S437. At step S437 the process advances to the locally owned apparatus control process in Fig. 45.

5 At step S450, in order to determine the status of the locally owned apparatus, the schedule of a user who is designated as a transmission source is confirmed by the PC 414, and it is ascertained that the user is at an outside location. Since the user is at an outside
10 location, at step S451 it is determined that a problem related to making urgent contact exists at the locally owned apparatus. At step S453 a check is performed to determine whether or not a printer that can output information is present at the user's destination. At
15 step S454 it is confirmed that there is a printer 412 that can output information, and it is determined that the printer 412 will be used to output the information. At step S455 the information is transmitted to the printer 412. At step S456 the users at the
20 transmission source and at the reception destination are notified that the job has been transferred.

 When, at step S443, there is no printer available to which to transfer the job but there is another apparatus that can be employed by the user, such as a
25 PC, a facsimile machine or a telephone, at step S444 it may be determined to perform the job by using one of the available apparatuses. Since the information can

not be transmitted unchanged, at step S445 the information to be output to the printer is converted into an electronic mail document or a facsimile document, or is changed to voice information for the output.

At step S446, depending on the medium used for the output, a notice that the job was transferred to another medium need not be issued, and can be transmitted by using the same medium. For example, when a telephone is used to transmit the information, it is better to notify a user of the job transfer before or after the transmission of the information.

Instead of the telephone, at step S443, the above PC, the facsimile machine or the telephone may be determined to be a suitable apparatus to replace the printer for the job. At step S447 the employment of such an apparatus may be determined to be an optimal plan that does not degrade the object of the job, and at step S448 the plan may be proposed to a user.

[Sixteenth Embodiment]

Fig. 49 is a flowchart showing the processing for this embodiment. Steps S498 to S500 are additionally provided for the flowchart in Fig. 43 as a process to be performed when there is no job. At step S498 the current operating statuses of other apparatuses are examined, and at step S499 a check is performed to determine whether or not a job that the locally owned

apparatus can perform is being held in another apparatus and not being performed. If such a job is being held in another apparatus, at step S500 the job is extracted from the pertinent apparatus and is
5 entered in the job table for the locally owned apparatus, while it is deleted from the job table for the pertinent apparatus. In this embodiment, therefore, an apparatus finds a job by itself and processes it.

10 Fig. 50 is a conceptual diagram showing the situation for this processing. Since no job is present in a printer 412, and a printer 413 has ten jobs in a queue, a printer 415 acquires a job from the printer 413 and processes it.

15 The process performed by the printer 415 is as follows. At step S492 there is no job, and program control moves to step S498. At step S498 the current statuses of the other printers, 412 and 413, are examined. At step S499 it is determined that at the
20 printer 413 there is a job that the printer 415 can execute. At step S500 the printer 415 extracts that job from the printer 413, and enters it in its job table. Then, the extracted job is deleted from the job table for the printer 413. Since at step S490 there is
25 no job input, and at step S492 there is a job that was entered previously, program control moves to step S493 to execute the job.

The operations for the performance of the job by the locally owned apparatus, which were explained in the fourteenth and the fifteenth embodiments, are performed, and the processing is thereafter terminated.

5 [Seventeenth Embodiment]

Fig. 51 is a diagram showing the transmission in this embodiment of a print job and other information in a system employing apparatuses. The heavy arrows are used to depict the transmission routes for the print
10 jobs, and the broken line arrows are used to depict the transmission routes for other information.

The print job in this embodiment includes parameters that are referred to during printing: the document to be printed; the number of print copies; the
15 print quality; and the print size. The other information includes the statuses, such as printing, normal, or out of paper, of individual printers, and a schedule for a print job processed by a print job scheduling unit.

20 In Fig. 51, in a client machine 510, a print job generation unit 512 generates a print job, and stores it in a print job memory unit 513. Then, the print job is transmitted by a print job transmission unit 514 in the client machine 510 to a server machine 511 for
25 managing printers.

In the server machine 511, a print job reception unit 516 receives the print job. When the parameters

of the print job have not yet been set, the print job is transmitted to a print job automatic setup unit 517, and when the parameters have already been set, the print job is transmitted to a print job automatic
5 change unit 518.

The print job automatic setup unit 517 sets print parameters while taking into consideration the urgency, economy and the quality that are acquired by the print job. The print job automatic change unit 518 can
10 perform the same process for changing parameters that have previously been set. The print jobs that are set or altered are registered in a print job schedule included in a print job scheduling unit 520 and are sequentially read to a print job transmission unit 519,
15 or the print job may be directly transmitted to the printer job transmission on the unit 519 from the print job automatic setup unit 517 or the print job automatic change unit 518. The printing is then performed.

The status, such as in printing, normal or out of
20 paper, of an available printer is acquired by a printer state acknowledgement unit 515, and is transmitted to the print job automatic setup unit 517 and the print job automatic change unit 518 where it is employed for the setup or change of the print job. Similarly, the
25 printing schedule for the print job included in the print job scheduling unit 520 is also transmitted to these units 517 and 518 for their employment.

As is shown in Fig. 51, a print job may be transmitted along a different route. When a machine for generating a print job is the same as a machine for managing printers, the print job may not be transmitted
5 via the print job transmission unit 514.

Fig. 52 is a flowchart showing the processing performed by the print job automatic setup unit 517. The print job automatic setup unit 517 automatically sets parameters within a range that satisfies a
10 designated quality and the printing can be performed as rapidly and as economically as possible.

In Fig. 52, at step S520 a factor for determining the printing time and the amount of consumed toner is initialized in preparing for the simulation. Then, at
15 step S521 a quality determination variable is initialized to a maximum quality value (e.g., 5), and at step S522 the period of time for the printing is simulated. At step S523 a check is performed to determine whether the simulated period of time for the
20 printing equals a specified value. When the time period for the printing equals a specified value, at step S524 the consumption of toner is simulated. At step S525 a check is performed to determine whether the simulated consumption of toner equals a specified
25 value. When the consumption of toner equals a specified value, the job is changed to the current quality determination variable value at step S526.

When, at step S523 or S525, the period of time for the printing or the consumption of toner is not equivalent to its specified value, at step S527 the quality determination variable is decremented by one.

5 At step S528 a check is performed to determine whether or not the resultant quality determination variable satisfies is equivalent to a designated quality. When the designated quality is satisfied, program control returns to step S522. When the designated quality is
10 not satisfied, the processing is terminated with an automatic setup disabled state.

Fig. 53 is a table showing the period of time for the printing and the consumption of toner for one character corresponding to different specified
15 qualities for the printers A521 and B522. These values may be fixed values inherent to individual printers, or may be dynamic variable values, which are averages obtained for printing periods or for consumption of toner that were measured in the past.

20 Fig. 54 is a diagram showing the contents of a print job that is to be output in this embodiment, and parameters that were designated by a user. In the system for the embodiment, the contents of a print job in Fig. 54 and the set-up parameters are collectively
25 called a print job. In this embodiment, calculated in terms of characters, 500 characters are employed as the printing quantity for the print job in order to

simulate the period of time for the printing and the consumption of toner. In addition, it is assumed that for urgency a user will designate a period of only one minute, and will keep the default values for economy and quality.

In the example shown in Fig. 54, when the print job automatic setup unit 517 is activated, at step S520 in preparing of simulation, a factor for determining the period of time for the printing and the consumption of toner is initialized. As defined in the table in Fig. 53, for example, the periods of time required for the printing of one minimum quality (= 1) character by the printer A521 and the printer B522 are, on average, 100 mS and 200 mS respectively, and the consumption of toner for one character are 100 mg and 200 mg.

Following this, at step S521 the quality determination variable is initialized to the maximum quality value (e.g., 5), and at step S522 the printing period of time for the printing is simulated. If, for example, the printers A521 and B522 are prepared for printing and no print job is scheduled in the print job scheduling unit 520, printing can be initiated immediately, and no waiting time is required. Thus, when the target print job includes 500 characters, as simulation, printer A takes 250 seconds to print the characters and printer B takes 500 seconds.

Then, at step S523 it is determined that this

condition does not satisfy the one minute urgency period that is specified by the parameter in Fig. 54, and at step S527 the quality determination variable value is decremented by one.

5 Since the quality is not specified in the parameter in Fig. 54, program control returns to step S522 for simulation of the period of time for the printing. When, as the result of the repetition of the above process, the quality is set to the minimum
10 quality of 1, the period of time for the printing by the printer A521 is 50 seconds, which satisfies the urgent figure. Therefore, the quality is set to the minimum quality determination variable value (= 1), and the processing is normally terminated.

15 If the quality is set to 2 or higher, it does not meet the parameters set by the user, and the processing is terminated as an automatic setup disable error.

[Eighteenth Embodiment]

20 Fig. 55 is a flowchart showing the processing performed by a print job automatic change unit 518. The print job automatic change unit 518 automatically changes a parameter within a range that satisfies a specified urgency and economy so as to print data having as high a quality as possible. When all the
25 specified parameters can not be satisfied, the most important designated parameter is satisfied and the others are changed as slightly as possible.

Fig. 56 is a diagram showing the contents of a print job that is to be output in this embodiment, and parameters designated by a user. In the system of the embodiment, the contents of a print job in Fig. 56 and the set-up parameters are collectively called a print job. In this embodiment, calculated in terms of characters, 500 characters are employed as the printing quantity for the print job in order to simulate the period of time for the printing and the consumption of toner. In addition, it is assumed that a user designates all of the parameters and particularly specifies that the quality is the most important.

In the example shown in Fig. 55, when the print job automatic change unit 518 is activated, at step S520 in preparing for the simulation, a factor for determining the period of time for the printing and the consumption of toner is initialized. As is defined in the table in Fig. 53, for example, the period of time required for the printing of one minimum quality (= 1) character by the printer A521 and the printer B522 are, on average, 100 mS and 200 mS respectively, and the consumption of toner for one character are 100 mg and 200 mg.

Following this, at step S551 the quality determination variable is initialized to the maximum quality value (e.g., 5), and at step S552 the period of time for the printing is simulated. If, for example,

the printers A521 and B522 are prepared for printing and no print job is scheduled in the print job scheduling unit 520, printing can be initiated immediately, and no waiting time is required. Thus, 5 when the target print job includes 500 characters, as simulation, printer A takes 250 seconds to print the characters and printer B takes 500 seconds.

Then, at step S553 it is determined that this condition does not satisfy the one minute urgency 10 period that is specified by the parameter in Fig. 56, and at step S556 the quality determination variable value is decremented by one.

Since, at step S557, the quality in the parameter in Fig. 56 is not satisfied, program control returns to 15 step S552 for simulation of the period of time for the printing. As a result of the repetition of the above process, even when the quality is the one (= 3) designated by the user, the urgency period can not be satisfied. When, at step S556, the quality 20 determination variable value is decremented by one, at step S557 the quality specified by the user is still not satisfied, and program control therefore moves to step S558. At step S558 a check is performed to determine whether the quality is the most important 25 parameter. When the quality is the most important parameter, at step S560 the print job is changed in accordance with the specified quality, and the

processing is normally terminated.

For a case where the urgency is specified as the most important, when the quality is set to the minimum quality of 1, the printing period for the printer A521 is 50 seconds, which conforms to the urgency setting. Therefore, the quality is set to the quality determination variable value (= 1), and the processing is normally terminated.

[Nineteenth Embodiment]

Fig. 57 is a diagram showing the transmission of a print job and other information in a system in this embodiment employing apparatuses. The thick arrows describe the transmission routes for print jobs and the broken line arrows describe the transmission routes for other information.

The print job in this embodiment includes parameters that are referred to during printing: a document to be printed; the number of print copies; the print quality; and the print size. The other information includes statuses, such as printing, normal, or out of paper, of individual printers, and a schedule for a print job that is included in a print job scheduling unit 520.

In Fig. 57, in a client machine 510, a print job generation unit 512 generates a print job and stores it in a print job memory unit 513. Then, the print job is transmitted by a print job transmission unit 514 in the

client machine 510 to a server machine 511 for managing printers.

In the server machine 511, a print job reception unit 516 receives the print job and transmits it to a
5 print job interpretation unit 571. The print job interpretation unit 571 interprets an instruction from a user that is included in the received print job, and converts the instruction into information, such as a parameter, that can be processed by the system. When
10 the parameters of the print job have not yet been set, the print job is transmitted to a print job automatic setup unit 517, and when the parameters have already been set, the print job is transmitted to a print job automatic change unit 518.

15 The print job automatic setup unit 517 sets print parameters while taking into consideration the urgency, economy and quality values that are acquired from the print job. The print job automatic change unit 518 can perform the same process to change the parameters that
20 have been set. The print jobs that are set or altered are registered in a print job schedule included in a print job scheduling unit 520 and are sequentially read to a print job transmission unit 519, or the print job is directly transmitted to the print job transmission
25 unit 519 from the print job automatic setup unit 517 or the print job automatic change unit 518. The printing is then performed.

The status, such as in printing, normal or out of paper, of an available printer is acquired by a printer state acknowledgement unit 515, and is transmitted to the print job automatic setup unit 517 and the print job automatic change unit 518 where it is employed for the setup or change of the print job. Similarly, the printing schedule for the print job included in the print job scheduling unit 520 is also transmitted to these units 517 and 518 for their employment.

As is shown in Fig. 57, a print job may be transmitted along a different route. When a machine for generating a print job is the same as a machine for managing printers, the print job may not be transmitted via the print job transmission unit 514.

In this embodiment, as is shown in Fig. 58A, the parameters of the print job are set ambiguously by using natural language. Fig. 58B is a diagram showing, relative to an input character string in the natural language, the meanings represented by character strings according to the parameters and the items required to complete the meanings. The print job interpretation unit 571 refers to the meaning corresponding to an input character string in the natural language in Fig. 58B and the item required to complete the meaning, and interprets the instruction given in the natural language that is received as a print job setup parameter as follows.

From the character string "Print" in the input natural language, "printing" is the action that is the object of the user according to the meaning of the character string. Further, it is assumed that the required item "object" indicates the contents of a print job that was input at the same time, and that "quality" and "number of sheets" should be designated at a portion in the input natural language that has not yet been interpreted. Thus, the character string "one copy for client and five copies for members" is interpreted as an instruction to print one "sheet" having a high "quality" and five "sheets" having a desired "quality".

The processes hereinafter performed by the print job automatic setup unit 517 and the print job automatic change unit 518 are the same as those in the seventeenth and the eighteenth embodiments.

[Twentieth Embodiment]

In this embodiment, as is shown in Fig. 59, the print job parameters are set based on the distribution destination described in a document, which is the contents of the print job, and on the number of sheets.

The action of the job is printing.

Printing for a "client" is interpreted as high quality printing, and the number of sheets is one.

"ABC project" is interpreted as a "member use" and the printing quality is arbitrary, the number of sheets

being five. A user acquires in advance information that he or she is a member of the ABC project.

The processes hereinafter performed by the print job automatic setup unit 517 and the print job automatic change unit 518 are the same as those in the

[Twenty-first Embodiment]

Fig. 60 is a diagram showing the transmission of a print job and other information in a system in this embodiment employing apparatuses. The heavy arrows describe the transmission routes for print jobs and the broken line arrows describe the transmission routes for another information.

The print job in this embodiment includes parameters that are referred to during printing: the document to be printed; the number of print copies; print quality; and print size. The other information includes statuses, such as printing, normal, or out of paper, of individual printers, and a schedule for a print job that is included in a print job scheduling unit 520.

In Fig. 60, in a client machine 510, a print job generation unit 512 generates a print job, and stores it in a print job memory unit 513. Then, the print job is transmitted by a print job transmission unit 514 in the client machine 510 to a server machine 511 for managing printers.

In the server machine 511, a print job reception unit 516 receives the print job and transmits it to a print job interpretation unit 571. The print job interpretation unit 571 interprets an instruction from a user that is included in the received print job, and converts the instruction into information, such as a parameter, that can be processed by the system. When the parameters of the print job have not yet been set, the print job is transmitted to a print job automatic setup unit 517, and when the parameters have already been set, the print job is transmitted to a print job automatic change unit 518. A print job simulation unit 601 simulates printing at the setup that is specified by the print job to acquire the period of time for the printing and the consumption of toner.

The print job automatic setup unit 517 sets print parameters while taking into consideration the urgency, economy and quality values that are acquired from the print job. The print job automatic change unit 518 can perform the same process to change the parameters that have been set. The print jobs that are set or altered are registered in a print job schedule included in a print job scheduling unit 520 and are sequentially read to a print job transmission unit 519, or the print job is directly transmitted to the print job transmission unit 519 from the print job automatic setup unit 517 or the print job automatic change unit 518. The printing

20250327 14:22:47

is then performed.

The status, such as printing, normal or out of paper, of an available printer is acquired by a printer state acknowledgement unit 515, and is transmitted to the print job automatic setup unit 517 and the print job automatic change unit 518 where it is employed for the setup or change of the print job. Similarly, the printing schedule for the print job included in the print job scheduling unit 520 is also transmitted to these units 517 and 518 for their employment.

As is shown in Fig. 60, a print job may be transmitted along a different route. When a machine for generating a print job is the same as a machine for managing printers, the print job may not be transmitted via the print job transmission unit 514.

Fig. 61 is a flowchart showing the processing performed by the print job simulation unit 601. First, at step S611, the print job simulation unit 601 initializes, in preparing for the simulation, a factor for determining the printing period and the consumption of toner. At step S612 the period of time for the printing is simulated at the setup that is also specified by the print job, and at step S613 the consumption of toner is simulated at the setup designated by the print job. In this manner, the period of time for the printing and the consumption of toner are acquired.

A specific method is the same as that explained in the seventeenth and the eighteenth embodiments.

[Twenty-second Embodiment]

In this embodiment, a plurality of output trays
5 are provided for a printer, and a tray is selected in consonance with a user.

Fig. 62 is a flowchart showing the processing for a printer system in this embodiment. When a printer system receives a print job, first it performs a
10 process for coping with a case where a plurality of print jobs are received at the same time, and then it initiates the processing shown in Fig. 62.

Figs. 63A and 63B are diagrams showing the external appearances of the printer systems in this
15 embodiment. As is shown, printers 631 and 632 each have a plurality of output trays: for the printer 631, each output tray is provided with a screen for displaying the name of the person to whom a document on the tray belongs; and for the printer 631, the names of
20 the persons whose document remain on which trays are displayed on a common screen. When a user is set in advance for each output tray, the individual trays are user dedicated trays. When the trays are not
25 specifically assigned, the users of the output trays are changed as needed.

The printer system in this embodiment implements the functions of notifying a user of the receipt of a

document, the termination of printing, and the failure to collect a printed document (uses a sensor).

The above processing will now be described. In Fig. 62, at step S621 information concerning a destination is acquired from information included in a print job. The information concerning the destination is obtained, as is explained in the twenty-ninth embodiment, either by interpreting the setup described in the print job, or by extracting it from information, such as E-mail, that is set separately from the contents of the print job. At this time, when, as in conventional use, a printer is employed as an output device for a personal computer, usually an addressee is not designated. When the printer is employed as a facsimile machine or for transmission of E-mail, as in the system in this embodiment, an addressee is normally designated.

At step S622 a check is performed to determine whether or not an addressee is designated. At step S623 the addressee is notified of the arrival of a document. At step S624 the addresser information is acquired from the information included in the print job. The addresser information is acquired, as is explained in the twenty-ninth embodiment, either by interpreting the designation described in the print job, or by extracting it from information, such as E-mail, that is set separately from the print job. When,

as in conventional use, a printer is employed as an output device for a common personal computer, normally the addresser falls within the control sphere of the system. However, when the printer is used as a facsimile machine, as in the system in this embodiment, usually the addresser is not within the control sphere. At step S625 a check is performed to determine whether the addresser is in the control sphere. At step S626 when the addressee is designated, a corresponding output tray is selected. When the addressee is not specified and only the addresser is specified, an output tray corresponding to the addresser is selected. At step S627 the addresser or the addressee information is transmitted to the corresponding output tray, as is shown in Fig. 63A. Or, as is shown in Fig. 63B, the addresser or the addressee information and the output tray that is employed are displayed on the common display. When the user is set for each output tray, the individual trays are user dedicated trays. When the trays are not specifically assigned, the users of the output trays are changed as needed.

At step S628 printing is executed. At step S629 a check is performed to determine whether the printing has been terminated and whether the addresser is within the control sphere. At step S630 the addresser is notified of the termination of the printing. At step S631 a check is performed to determine whether a

document has been left for a predetermined period of time and whether the addresser is in the control sphere. At step S632 the addresser is notified that a printed document has been left in the tray for an
5 extended time period.

[Twenty-third Embodiment]

In this embodiment, information concerning the time is handled. Fig. 65 is a diagram showing the functional arrangement of a system according to the
10 embodiment. A processor 650 includes an understanding unit 652, a planning unit 653, an execution unit 654, a response unit 655 and a knowledge base 656, and is connected to a database 651.

Fig. 64 is a flowchart showing the processing
15 performed by the functional arrangement in Fig. 65 in this embodiment.

At step S640 a check is performed to determine whether or not there is external input. If so, at step S641 the understanding unit 652 employs the knowledge
20 base 656 to analyze an input document as the units of words and sentences, and at step S643 the object of the input contents is analyzed and ascertained. At step S644 a check is performed to determine whether information required for an understanding of the object
25 is insufficient. If the information is unsatisfactory, at step S645 a query is issued to a user, and a response from the user is studied in the knowledge base

656. Program control thereafter returns to step S643. If the information is adequate, program control moves to step S646. When, at step S640, there is no input, at step S642 a job to be executed is found and program
5 control advances to step S646.

At step S646 the planning unit 653 prepares a plan to achieve the object. At step S647 a check is performed to determine whether information required for planning is insufficient. If the information is
10 unsatisfactory, at step S648 a query is issued to the user, and a response from the user is studied in the knowledge base 656. Program control thereafter returns to step S646. If the information is adequate, at step S649 the execution unit 654 executes the plan. At this
15 time, the execution unit 654 accesses the database 651 or communicates with another application, as needed. At step S650 the response unit 655 determines whether or not a response should be made. If a response should be made, a decision is made concerning the selection of
20 the contents for the response. Further, at step S651 a response is prepared in accordance with the selected contents, and is transmitted to the user.

The understanding unit 652 acknowledges, as needed, externally input information, such as keyboard
25 input, voice input, E-mail or facsimile or news information, analyzes the received information and also the time concept contained in the words in sentences,

and obtains an understanding of the contents of the sentences that are concerned with time.

Fig. 67 is a diagram showing an example where schedule information is extracted from electronic mail.

5 In the above process, specifically, as is shown in Fig. 67, the contents of a document received by E-mail are analyzed, and the time concepts such as "February 22nd", "13:00" and "15:00" are found and analyzed. Then, an understanding of the sentence concerning the
10 concept, "We have scheduled a patent system explanation meeting at conference room B from 13:00 to 15:00 on February 22" is obtained, and an action associated with the time can be correlated with the schedule.

The analyzed time concept is compared with the
15 current time. If the time concept describes the future, a corresponding action is registered in the schedule, but if the time concept describes the past, it is abandoned without being registered or it is registered as an information of a type other than that
20 for a schedule, such as information for a personal data base, that is used to record past events.

The understanding unit 652 analyses the contents of externally input information, such as keyboard input, voice input, E-mail, facsimile or news
25 information. When the understanding unit 652 finds in the sentences a term (a word or a concept) that is unknown to the system, or a plan that the system has

5

10

15

20

25

object. The planning unit 653 prepares a plan of an action for the system to take to achieve the object. The execution unit 654 performs the processing. And the response unit 655 notifies a user of the results of the processing.

When, for example, it is ascertained, from information concerning an addresser, upon the receipt of the E-mail message shown in Fig. 67 that the mail is from an addresser who is not registered in the database, information concerning the addresser is extracted from the message and is registered in the personal database in the database 651. Further, when more information is obtained concerning the addresser who is not registered in the personal database, the information may be registered in the personal database.

Since the understanding unit 652 understands the message is for a notice for an explanation meeting, it accesses the schedule of a user in the database 651, and compares new schedule data with the current schedule data. When the new schedule data and the current schedule data do not conflict, the new data are additionally registered in the schedule. However, as is shown in Fig. 69, when the schedule data conflict, a reply to the addresser and a notice for a user are prepared.

As is described above, since this system understands the contents of received information, the

2025 RELEASE UNDER E.O. 14176

system can prepare a response in consonance with the situation and execute it.

In the above explanation, the system prepares a reply to a user who sent the E-mail without confirming it with a user, and transmits the reply. This is because the sentence, "Please contact me as soon as possible if there is any difficulty" is in the message, and as a result of the analysis of this sentence, it is determined that a response is very urgently required. If the urgency of a response is determined to be low because a date for the holding the meeting is fairly advanced and the attendance at the meeting is arbitrary, the system confirms it with a user before transmitting a response. In other words, the system determines in which action to take in consonance with the degree of urgency.

In addition, the schedule or the personal database can be accessed to transmit a response, relative to the input of the natural language by a user, as well as a natural language instruction received from a user.

For example, the personal database can be accessed by asking the natural language question, "What is the telephone number of Mr. XX?". Or the schedule can be accessed when the natural language question, "Where will the meeting on the 16th be held?" is received, to send a reply to a user.

Fig. 66 is a diagram showing the input/output

2025 RELEASE UNDER E.O. 14176

types between the system that performs the overall processing in this embodiment and external devices.

Input data can be data input via a keyboard, natural language information received by E-mail, documents or pictures input as images by a scanner, voice input via a microphone or images input by a camera. A character recognition process is preformed for a document that is read by the scanner, or a voice recognition process is performed for speech, so that input information in natural language can be obtained.

As for when there is no input (idle state), as is shown at step S642 in Fig. 64, when there is no external input the system searches for a job that it should execute and regards it as input. In the idle state, when no job is given to the system, the system, for example, accesses news and aggressively acquires as input information concerning the user.

As for output, there are the registration of a schedule in a database, the filing or erasure of data relative to a file memory device, or the dispatch of a notice to a user or a reply to an addresser. The importance of the output is that it can be determined that a process can not be performed within the control range of a system, and another action, such as transmitting a response to that effect, can be performed.

An input/output destination is a user or an

external device, or a different processor in the system or another application.

In addition, input documents are analyzed, and data concerning a person and data concerning the time
5 are extracted and stored in the personal database and the schedule database. Also, data required for the anticipation of an action is extracted to use for planning.

In the example in Fig. 67, as a result of analysis
10 of an E-mail document that is input, the following description concerning a person is acquired:

To: toshima@abc.canon.co.jp,
rohra@abc, canon.co.jp,
kazuyo@abc.canon.co.jp

15 From ichiro@abc.canon.co.jp

I am Suzuki of system promotion section.

Suzuki (ichiro@abc.canon.co.jp)

044-123-4569 (ext. 654-3210)

Canon Inc. Intellectual Property Head Office System
20 Promotion Section

Assuming that a person whose mail address is
"kazuyo@abc.canon.co.jp" is already registered in the personal database and the other persons are not registered, as is shown in Fig. 67, data for PERSON 1,
25 2 and 3 are extracted and registered in the database 651.

Since there is a description concerning the time,

"We have scheduled a patent system explanation meeting at conference room B from 13:00 to 15:00 on February 22" data for EVENT1 is extracted.

Further, since there is a description used for
5 estimating an expected action, "Please contact me as soon as possible if there is a difficulty" this is used for the processing to be explained while referring to Fig. 70.

Fig. 68 is a specific flowchart for step S649
10 prepared by extracting the portions from the flowchart in Fig. 64 that are required for performing the processes in Figs. 67 and 69.

The processing will now be explained while referring to Figs. 67 and 69.

15 At step S680 E-mail is input and at step S681, of each word and sentence, the input E-mail document is analyzed. At step S683 it is ascertained from a signature and a header that "there is information concerning persons" and "an event, an explanation
20 meeting, will be held". Further, it is ascertained that "a reply is requested if there is a difficulty".

At step S684 the data concerning a person is extracted and a plan for registering the data in a database and a plan for registering the explanation
25 meeting event in the schedule are made. At step S685, it is ascertained that there is a plan to be executed. At step S686 it is found that there is no problem with

2025 RELEASE UNDER E.O. 14176

the plan, and program control thereafter moves to step S688. At step S688 the data concerning the person is extracted and registered in the database, and program control returns to step S685.

5 In Fig. 67, at step S685 there is a plan to be executed: registration of the explanation meeting event in the schedule. At step S686 it is assumed that the event can be registered in the schedule with no problem, and program control goes to step S688. At
10 step S688 the event is registered in the schedule, and program control returns to step S685. At step S685 there is no other plan to be executed, and at step S689 no acknowledgement receipt is required. The processing is thereafter terminated.

15 In Fig. 69, at step S685 there is a plan to be executed: registration of the explanation meeting event in the schedule, and at step S686 a conflict is found in the schedule. Since there is a problem with the execution of a plan, at step S687 a reply to that
20 effect is transmitted and a plan is made to notify a user that there is a problem. At step S685 there is a plan for writing a reply and transmitting it, and at step S686 no problem concerning the execution of the plan is found. At step S688, therefore, a reply
25 indicating that the timing is inconvenient is prepared and transmitted to the addresser. At step S685 there is a plan for preparing a document for notification of

a user. At step S686, there is no problem in execution, and at step S688 a response to a user is prepared describing that a reply was sent for re-consideration because of the contents of the E-mail and the conflict of the schedules. At step S685 there is no plan to be executed and at step S689 since there is an notice to a user, it is transmitted to the user. The processing is thereafter terminated.

In the example in Fig. 69, when the schedule information EVENT1 that is extracted is compared with the schedule EVENT2 that is planned previously, it is found that the two events conflict. Further, according to the information extracted in the example in Fig. 69, it is apparent that a reply is necessary if there is a difficulty. In the system in this embodiment, the knowledge for preparing letter is employed to write a letter describing that a user can not attend the meeting because the schedules are conflicting, and the reply is automatically transmitted.

In addition, the user of the system in this embodiment is notified that the system automatically has transmitted a reply for the user.

[Twenty-fourth Embodiment]

Fig. 70 is a diagram showing an example where a user sends a question by voice to a system according to this embodiment.

When a user asks by voice "where will tomorrow's

conference be held?", the system can examine the schedule information of the user and tell the location of the conference.

When the user does not know how to get the location for the conference and asks "In which area in Shimomaruko?", the system examines the database, performs planning for an explanation to make a user understand, prepares a briefing story, and uses graphical images and sounds to explain how to get the location.

Fig. 71 is a flowchart showing the processing performed in Fig. 70 by referring to the basic flowchart in Fig. 64. An external input is regarded as a query.

The processing relative to a first inquiry will be explained. At step S710 voice (where will tomorrow's conference be held?) is externally input, and at step S711 the input sentence is analyzed. At step S712 it is understood that the input sentence is an inquiry for the conference, and that the object of the user is to know the location of the conference. At step S713 the following planning is performed to answer the inquiry. (1) Tomorrow's schedule is extracted. (2) The location registered in the schedule is acquired. (3) A reply is prepared to tell the acquired location.

At step S714 information is sufficient and program control moves to step S716. If the schedule show a

plurality of conferences, the system does not identify which conference is. Therefore, at step S715 a query is sent to a user to remake a plan. At step S716 the plan made at step S713 is executed, and a reply
5 document to the user is prepared. At step S717 it is ascertained that there is a response to the user, the system determines the transmission of the response. At this time, since it is understood that the input was done by voice, transmission of the reply by voice is
10 also determined. At step S718 the response, which is voice data obtained by conversion, is transmitted to the user.

The processing is temporarily terminated, and following this, an inquiry from the user is input. The
15 process relative to the second inquiry will now be described.

At step S710, voice (In which area in Shimomaruko?) is input externally, and at step S711 the input sentence is analyzed. At step S712 it is
20 understood that this inquiry is a continuous question of the first one, and also that a specific location of the place name that was answered is being asked.

At step S713 the following plans are made to respond the question: (1) a plan for explaining that
25 it is difficult to explain the location by writing; (2) a plan for explaining the location by sequentially sending images; (3) a plan for acquiring necessary

images from an image database and a location database;
and (4) a plan for preparing sentences corresponding to
images.

At step S714 the information is adequate, and at
5 step S716 the plans made at step S713 are sequentially
executed and a reply to a user consonant with the
images is prepared. At step S717, since there is a
reply document to be transmitted to the user, the
transmission of the response is determined. At this
10 time, it is understood that the input was done by
voice, so that it is also determined that explanation
will be given by voice while displaying images on a
monitor. At step S718 the response is transmitted to
the user. The processing sequence in Fig. 70 is
15 thereafter terminated.

[Twenty-fifth Embodiment]

In an example shown in Fig. 72, when two scheduled
events conflict, the order of priorities of the two
events is obtained from a comparison, and a plan to
20 handle this problem is prepared and proposed to a user.

That is, in this example, when one schedule is
found to be more important than the other, it is
proposed that the less important schedule be canceled.

If the user knows somebody to send as his or her
25 proxy to the scheduled event for which cancellation is
proposed, the user can send the system a response to
that effect. The system can then perform an action in

consonance with the response. Also, the system can study a plan for despatching another person as a proxy.

In Fig. 72 is shown a combination of other methods performed at step S646 in Fig. 64 to make plans when
5 the schedule conflict is found at step S686 in the flowchart in Fig. 68.

The processing in Fig. 68 has been explained for unconditionally transmitting to a user a response for an inconvenience. In this embodiment, the processing
10 for a plurality of plans is employed as the re-planning method at step S646.

Fig. 73 is a flowchart for evaluating a priority extracted from the contents of a document and for proposing it to a user. The processing will now be
15 explained.

The priorities of the scheduled events is determined by using information that the user has set in advance for each schedule, attendance at an event included in the schedule, the object of a scheduled
20 event and the result obtained as a result of the analysis of the received document. A user may set the priorities of persons that are expected to attend the pertinent event.

The priority determined according to the object of
25 the schedule may be set in advance by a user, or may be determined while taking into account the object or the field that the system understands, from the study of

the past, that the user is interested in. That is,
when the user engages in computer associated work, the
schedule for a computer associated event priority over
an event associated with real estate. Of course, if a
5 user plans to purchase a house and that data is stored
as information concerning the user, the schedule of an
event associated with real estate may take priority.

For the priority determined from the result of the
analysis of the document, when a document including the
10 sentence "Please be sure to attend the meeting" and a
document including the sentence "Please attend the
meeting if possible" setup a conflict, the first
document received is determined to take priority.

In Fig. 73, at step S730 the current schedule
15 information is acquired. At step S731 the priority for
new schedule information is evaluated. At step S732
the priorities of both schedules are compared. At step
S733 from the result of the comparison, a plan is made
to prepare a notice for querying a user (e.g., display
20 two conflicting scheduled events and ask whether the
event having the lower priority can be canceled). At
step S734 the prepared notice is transmitted to the
user. At step S735 a response from the user relative
to the inquiry concerning the plan is acquired. The
25 same re-planning process as in Fig. 68 is performed to
again prepare a plan by using the response obtained
from the user so that an action consonant with the

2025 RELEASE UNDER E.O. 14176

response of the user can be taken.

Fig. 74 is a flowchart showing the re-planning process.

At step S740 the response finally obtained in Fig. 73 is regarded as input. At step S741 the input sentence is analyzed. At step S742 it is ascertained that the schedule is to be changed and that this is the first instructed plan.

At step S743 the following plans are made: (a) the changing of the schedule; (b) the preparation of a document to transmit the schedule to a proxy; (c) the study of a new plan; (d) the preparation of a document to transmit the new plan to the user; and (e) the notification sent to a user concerning another schedule that should be recalled.

At step S744 the plans made at step S743 are executed: (a) the schedule is changed; (b) a document is prepared to transmit the schedule to a proxy; (c) a new plan is studied; (d) a document is prepared to transmit the new plan to the user; and (e) a user is notified of another schedule that should be recalled.

At step S745 the notification document is transmitted to the user. The processing for performing the process in Fig 72 is thereafter terminated.

[Twenty-sixth Embodiment]

Fig. 75 is a diagram illustrating the overall image of a system according to this embodiment,

including input/output devices. Fig. 76 is a flowchart showing the processing performed by the system in Fig. 75.

Information input by E-mail, by voice, via a
5 keyboard, across the WWW, and by input devices, such as
a telephone, a facsimile machine, a scanner and a
camera, is analyzed by an input management unit 751
(step S760). A core unit 752 ascertains the contents
of the information and plans an appropriate process
10 (step S761). An output management unit 753 determines
an output medium and prepares the contents to be output
and an output route (step S763). Then, the information
is output by E-mail, by voice, across the WWW, or by
output devices, such as a telephone, a facsimile
15 machine, a printer and a copier.

Figs. 77 to 79 are specific flowcharts showing the
process at step S760 (the process performed by the
input management unit 751), at step S761 (the process
performed by the core unit 752) and at step S763 (the
20 process performed by the output management unit 753).

In Fig. 77, when, at step S770, it is determined
that there is new input, at step S771 the input
information is obtained. At step S772 the input
information is analyzed, as needed, after the
25 information has been identified. At this time, the
input management unit 751 accepts information from
various media and identifies or analyzes the data using

methods corresponding to the individual media.

In Fig. 78, the core unit 752 receives the information that is analyzed in Fig. 77.

At step S780 the object of the input information
5 is analyzed and ascertained from the result of the
analysis. At step S781 how the object of the input
information is related to the main apparatus (the
system or the user) is examined. At step S782, from
the relationship with the main apparatus, planning for
10 what to execute is performed in consonance with the
object. At step S783 the plan made at step S782 is
executed.

In Fig. 79 the output management unit 753 employs
the results obtained in Fig. 78 to determine whether a
15 response is needed. If a response is required, it is
prepared and output.

At step S790 the result obtained in Fig. 78 is
analyzed. At step S791 a check is performed to
determine whether or not there is a response relative
20 to the results. When there is no response, the
processing is thereafter terminated. If there is a
response, at step S792 a response relative to the
external response is determined. At step S793 a medium
for the response is determined. At step S794 a
25 response is prepared in consonance with the designated
medium. At step S795 the prepared response is issued
by the designated medium. At step S896 the response is

actually output. The processing performed by the arrangement in Fig. 75 has been explained.

When, for example, E-mail is received that notifies the user of the holding of a conference, the input management unit 751 analyses the input
5 information according to the procedures in Fig. 77. From the obtained result, the core unit 752 prepares a plan, according to the procedures in Fig. 78, as to how the user and the system should handle the information.
10 The plan is transmitted to the output management unit 753, which in turn performs the process according to the procedures in Fig. 79. When a response should be transmitted with the plan, a response is actually prepared and transmitted.

15 Depending on the contents of the conference described in E-mail message and the status of the schedule of the user, at step S782 a plan is prepared for the aggressive transmission of the response to the user, so that preparation of the response is required.
20 At step S791, therefore, it is determined that a response is to be transmitted. At step S792 the contents of the response are determined. When the schedules conflict and when it is uncertain which schedule should be selected or whether a user intends
25 to attend a specific conference, the contents of a response asking for a decision are determined. At step S793 a medium is selected by which the contents of the

response can be transmitted most effectively. When,
for example, the user is outside the office, a medium,
such as a telephone or a facsimile machine, is selected
that can issue a notice to the user. When the user is
5 being operating a personal computer, a medium, such as
a personal computer, is selected that can effectively
display various reference materials. At steps S794 and
S795 a document and an image are prepared in consonance
with the contents and the medium that are decided
10 above, and a response is prepared using a method for
converting the data into voiced natural language in
consonance with a specific medium, and is issued.

Fig. 80 is a detailed flowchart for Fig. 75 to
explain the processing for extracting data from input
15 information. In this system according to the
embodiment, when a document is input, at step S801 type
identification symbols, such as the layout and a bar
code of a document, are employed to infer the document
type. If the document is inferred to be a letter, a
20 report or a patent publication, program control moves
to step S803. When no identification of the document
is possible, program control goes to step S810 whereat
OCR is thoroughly performed to ascertain the document
type.

25 At step S803, in order to confirm the inferred
document type is correct, a characteristic block is
interpreted by the OCR to identify the document type

SECRET E08655

(see Figs. 82A and 82B). At step S804 the addressee of
a letter and the patent serial number of the patent
publication are found and the document type is
confirmed. When the confirmed document type matches
5 the inferred document type, program control advances to
step S806. If the document types do not match, program
control moves to step S810. For slips, at the top of
which character strings describing the slip type are
printed, the document type can be easily determined by
10 the OCR on the employing upper portion of the sheet.

At step S806 the knowledge base of the document
type that has been confirmed is employed to read and
interpret a specific block using OCR. At step S807 a
check is performed to determine whether there was
15 information in the past that concerns the resultant
information. If such information was present, program
control moves to step S808. If such information was
not present, program control goes to step S810. As a
result, the addressee or the patent number is found and
20 whether the information is a reply to a letter that was
sent in the past can be ascertained.

At step S808, based on the identified status, the
object is decided from the contents of the important
text, and at step S809 a process to be executed is
25 determined.

At step S811, because of the above object, the
information is analyzed in another range where OCR has

not yet been performed. At step S812 a required process is actually performed. As a result, a filing process, etc., is performed as needed.

In the above process, the OCR can be performed
5 while inferring the contents of the information, more efficient and precise OCR results can be obtained than when, as in the conventional case, the OCR use is effected from the beginning. Accordingly, the process based on the OCR results can be performed precisely.

10 Fig. 81 is a diagram showing an example letter/facsimile that is a target for data extraction.

In this example, at step S801 the document type is inferred from the layout of a document. As a result, DocType1 = letter/fax.

15 At step S803 a specific block is read by the OCR and is interpreted (see Figs. 82A and 82B). Then, "From", "To" and "Dear Sir" are acquired, and at step S804 DocType2 = letter/fax.

20 The process for reading a specific block by using OCR, which was explained at step S803 in Fig. 80, will be specifically described. Figs. 82A and 82B are diagrams for explaining this process.

The system in this embodiment scans a specific block as follows:

25 (1) A specific block is read fast by pre-scanning with a low resolution.

(2) A form of the information that is read is compared

DocType1 = letter/fax

with an information form stored in a DB 823. When the forms match, input information other than the form, or information in an area (e.g., inside the frame of a card in Figs. 82A and 82B) specified for each form, is read at a high resolution.

(3) Only the area that is read is regarded as an OCR target and analyzed, and the processing is continued.

In addition, since in this example it is assumed that there are a plurality of cards having the same form, documents that are to be read at a predetermined interval probably have the same form. Therefore, first, the process is performed while it is assumed that the documents have the same form, and when a contradiction occurs, it is assumed that the documents have different forms and a re-analysis of them is performed.

As a result, the processing speed is considerably increased, the analysis range is limited, and an analysis domain is determined by specifying a form, and the analysis precision is drastically improved.

The determination of the object from the contents of the information, which was explained at step S808 in Fig. 80, will be specifically described.

The system in this embodiment employs date data to perform the determination process according to the procedures in Figs. 83A and 83B. When a sender is a user, the following process is performed.

(2) When the date is yesterday or some time in the past, the user is queried as to whether the same

(3) When the date is tomorrow or some day in the future, the user is queried in order to determine whether the information should be held until the designated date, or whether the user made a mistake.

```
(1)  Date1 = November 25, 1996 & Date2 = November 25,
1996 -- send the document
```

20 (3) Date1 = November 25, 1996 & Date2 = November 26,
 1996

Figs. 83A and 83B are flowcharts showing the processing for analyzing the object extracted from an input document. When a document is input, at step S830 a check is performed to determine whether the sender is

a user. If the sender is a person other than a user, the input document is determined to be a received document. At step S831 a corresponding object, such as filing or data extraction, is examined, and the
5 processing is thereafter terminated.

When the sender is a user, program control advances to step S832 to analyze the type of the input document. At step S833 the date of the document is compared with the current date. When the two dates are
10 close to each other, at step S835 a check is performed to determine whether the document was transmitted before. When the document was not transmitted before, its object is determined to be "transmission of a document". If the same document was transmitted
15 before, at step S843 the object for filing or re-transmission is extracted.

When the date of the document is a fairly old date, program control moves to step S836, whereat a check is performed to determine whether or not the same
20 document was transmitted before. When the document was transmitted before, program control moves to step S843. When the document was not transmitted, program control goes to step S837 whereat a check is performed to determine whether any other date is described in the
25 information for the document. When there is another date, program control goes to step S843. When no other date is found, it is ascertained that the object can be

When the date of the document is a date fairly far in advance, at step S840 a check is performed to determine whether any other date is described in the information for the document. When, at step S841, there is another date, the object is determined to be "transmission of the document". When no other date is found, program control moves to step S839.

Fig. 84 is a diagram showing an example arrangement of a system according to this embodiment. In this embodiment, the system serves as a current facsimile machine.

As a result, appropriate information can be transmitted to a printer or a facsimile machine, by E-mail or via the WWW.

25 Fig. 85 is a diagram illustrating an example
arrangement of a system according to this embodiment.
In this example, the system implements a desk sorter

function for processing all the kinds of documents on the desk.

That is, in consonance with the contents of the document that is read, sorting, filing, scheduling,
5 data extraction and automatic processing are performed.
[Twenty-ninth Embodiment]

Fig. 86 is a detailed diagram for explaining the system in Fig. 85. The processing performed by the system shown in Fig. 86 will be specifically described
10 while referring to the flowchart in Fig. 87.

Fig. 87 is a flowchart showing the processing for this embodiment. Figs. 88 and 89 are tables for knowledge used during the processing; the table in Fig. 88 shows the knowledge in general knowledge base, and
15 the table in Fig. 89 shows the knowledge in a knowledge base of a field specified on a cover sheet. In this embodiment, information defined in the tables in Figs. 88 and 89 is employed to compare a character string included in an input document with a character string
20 defined in a character string column in the table, and the conception in a corresponding column, a Role for further specifying the meaning, and a Condition for specifying succeeding information, or an instructed process Action are acquired, and analysis for them is
25 performed.

In Fig. 87, at step S870 a cover page is scanned and an OCR process is performed. At step S871 the

knowledge base in Fig. 88 is examined to extract from it data, such as the names of a sender and a receiver and their telephone numbers and facsimile numbers. At step S872 the obtained data are registered in a

5 database. In the example in Fig. 86, character string "To: Macrohard Corp." is included in the cover page of a received document. When this character string is compared with an item defined in the character string column in Fig. 88. Then, matching item "To" is found

10 and its Role is a reception company name or an individual name, so that "Macrohard Corp." is extracted as information concerning a receiver.

At step S873 a notification method and means, a filing job, an action for a place, and a job are

15 extracted. In the example in Fig. 86, character string "File: MH/Contract" is included in the cover page of the received document. When this character string is compared with the items defined in the character string column in Fig. 89, matching item "File" is found,

20 filing is extracted from the column as an instructed action, and "MH/Contract" is extracted from the document as information for a filing place.

Assuming that Date1 = November 25, 1996 and Date2 = November 25, 1996, as is explained in Figs. 83A and

25 83B, it is determined that the object is transmission of a document.

At step S874 a check is performed to determine

whether an action for the object of the processing is present. Since the transmission of the document to a receiver is the object, at step S875 a transmission action is performed. At step S876 the information on
5 the cover page is employed to determine whether the filing is necessary. Since the filing is required in the example in Fig. 86, at step S877 the document is filed at the instructed place, "MH/Contract".

At step S878 as well as at step S876 the
10 information on the cover page is employed to determine whether or not a notification for the transmission of the document should be issued to the sender. Since it is instructed to notify the sender, by voice, of the transmission of the document, at step S879 the sender
15 is notified by voice of that the document has been transmitted to the receiver. At step S880 whether or not another action is determined. At step S881 a keyword is designated, and an index is prepared by using keyword ABC.

20 [Thirtieth Embodiment]

Fig. 90 is a diagram showing an example processing where the history in the past is referred to based on an instruction by voice in natural language. The processing in Fig. 90 will be explained while referring
25 to the flowchart in Fig. 91.

Fig. 91 is a flowchart showing the processing for this embodiment. When an aural instruction "Fax

Contract again to John. Notify him by Phone" is received from a user, the system analyzes the object of the instruction in the natural language, and understands "Re-transmit document "Contract" to John, and Notify him of the transmission". Thus, the processing in Fig. 91 is initiated to specify the document Contract and the addressee John.

Since re-transmission means that the document was previously transmitted, at step S910 history information is acquired from the database. Then, the document Contract and the addressee John are specified from the history information. At step S911 the address of the John is obtained from the personal database. Since, in the database, there are two Johns, John Smith and John Bush, ordinarily the addressee can not be specified. Since at step S910 the history information is referred to, however, it is judged that John to whom the document Contract was transmitted is John Smith, and the addressee is thus specified. At step S912 the document "Contract" is acquired from the filing database. At step S913 the document is transmitted to addressee John. Since there is notice instruction "Notify him by Phone" at step S914 it is determined that transmission of the notice is necessary. At step S915, as well as in Fig. 89, according to the rule of the knowledge base, an instruction is issued to a facsimile machine 901 as a reception apparatus to send

a notice to a receiver by phone. At step S916 the other actions are not instructed, and program control thereafter determined.

Upon the receipt of the document, according to the notification instruction, the facsimile machine 901 notifies John by phone of the receipt of the document from Mr. Doors. When the facsimile machine 901 can not notify the addressee by phone of the receipt of the document, the addressee may take its place.

[Thirty-first Embodiment]

Fig. 95 is a flowchart showing example processing where, from the contents of a document that is input and analyzed, it is determined that a user should do something, a query is actually transmitted to the user, and a required process is preformed automatically. Fig. 92 is a diagram showing an example input document. Fig. 93 is a diagram showing the contents of a conversation between a system and a user. Fig. 94 is a diagram showing a document that is prepared by the system as the result of judgement of the conversation in Fig. 93.

The processing for preparing an output document in Fig. 94 from an input document in Fig. 92 will be described while referring to the flowchart in Fig. 95.

At step S950 the input document in Fig. 92 is analyzed and the following objects are understood: (a) Mr. John Smith arrives at Yokohama at three o'clock on

November 28; (b) Mr. John Smith little understands Japanese; and (c) some one should meet him at the station.

At step S951 what the user should do is determined
5 from the contents that are obtained. Since it is
determined that some one must meet him at the station,
program control advances to step S952. At step S952 a
check is performed to determine whether a proxy
(system) may execute the action. Since the system can
10 not meet him at the station, program control goes to
step S953. At step S953 a check is performed to
determine whether an inquiry should be issued to the
user, and if so, program control moves to step S954.
In this example, since it is determined from the
15 addressee of the input document that this is a request
for Dr. Aruna Rohra, program control moves to step
S954.

At step S954 a process for inquiring the user (Dr.
Aruna Rohra) is performed. In this case, as the result
20 obtained at step S951 the user must meet John at the
station, and an inquiry what to do is issued to the
user. At step S955 what to do next is determined from
the result of the inquiry, and whether or not an action
is to be initiated is determined. In this example, the
25 user instructs to ask Mr. Tanaka to meet him, the
action is initiated according to the instruction.
Since there is a request for Mr. Tanaka to act as a

proxy, it is assumed that the action must be initiated. At step S956 a document for requesting Mr. Tanaka as a proxy is prepared and a contact is made with Mr. Tanaka. In this example, an electronic mail document is prepared and transmitted. In this example, information that John arrives on 28th, an instruction for meeting him for the user and the original document that caused the request are attached to automatically form the document.

As is described above, processing has been explained for performing the matter (meeting John at the station) where from the input document the user must actually perform an action.

[Thirty-second Embodiment]

Fig. 96 is a diagram illustrating a thirty-second embodiment where a system is operated by a controller.

According to the system in this embodiment, devices and a controller directly or indirectly communicate with each other to specify the other.

Therefore, the following functions are provided:

- (1) automatic specifying of a device;
- (2) acquisition of a device capability from the device;
- (3) a UI (User Interface) inherent to a device;
- (4) operation by voice;
- (5) common basic operation for all the devices;
- (6) a UI inherent to a user; and
- (7) a UI having a high degree of freedom in consonance with the status.

That is, (1) only when a controller faces an

operating target device, it automatically recognizes the target device; (2) information for each device is acquired from the pertinent device via IrDA or via a wireless LAN; (3) a UI inherent to each device is
5 provided from the information for the device; (4) an operation by voice can be performed; (5) common basic operation can be provided by using the same controller; (6) user identification information is employed to acquire necessary information for each user from the
10 database or the address book and to implement the UI inherent to the user; and (7) the optimal UI is provided in consonance with the status.

In Fig. 96 since a controller 960 faces a facsimile machine 963, it acquires model identification
15 information from the facsimile machine 963, and renders a UI, which corresponds to the model, active. Then, following the displayed "Fax to" character string "Fax to John" is input with a touch pen, and transmitted to the facsimile machine 963. John's facsimile number is
20 read from an address book 965 in a personal computer 964, and a document set in the facsimile machine 963 or a document designated on a file in the personal computer 964 is transmitted to the fax number. The detailed processing will be described later.
25 [Thirty-third Embodiment]

Fig. 97 is a diagram showing a status monitor.

In a system according to this embodiment,

information of an apparatus that is other than the apparatus that a user directly operates can be referred to.

Therefore, the following functions can be provided: (1) remote and handy management; (2) specifying of automatic device; (3) common input/output for examining a status; (4) the same function as a portable telephone; (5) operation by voice; and (6) handling of all the devices that can input/output infrared rays.

That is, (1) required information can be acquired even from a remote area from a target device; (2) only when a controller faces the target device, it can automatically recognize the target device; (3) common basic operation can be provided by using the same controller; (4) the usability is enhanced by providing the portable telephone function for the controller; (5) operation by voice can be performed; and (6) the common protocol is employed to cope with all the devices that can input and output infrared rays.

In Fig. 97, a status monitor 970 selects a printer 961, a copier 962 or a facsimile machine 963, and character string "Status" is input with a touch pen and instructed. The status monitor 970 retrieves status information from the device that the status monitor 970 faces, so that the user of the status monitor 970 can confirm the statuses of the devices. Even when a

personal computer 964 is located at an area where a command from the status monitor 970 can not reach, the status of the personal computer 964 is requested to a printer 961, which can communicate with the personal computer 964 via the network. Then, the status information can be retrieved to the status monitor 970 from the personal computer 964 via the network and the printer 961.

[Thirty-fourth Embodiment]

Fig. 98 is a diagram showing an example where a controller 960 recognizes a target model, and a corresponding UI is read from the controller 960 and displayed. The controller 960, which does not face a target device, has a default screen on which message "Select a device which you would like to use" is displayed, as is shown in the center in Fig. 98.

The communication between the controller and the target model will now be described. It should be noted that (2) and (3) are not necessarily required. When, for example, in (4) a target model generates a signal to the controller at predetermined intervals, the same effect can be obtained. The positional relationship between the controller 960 and a target model may be employed to determine that the controller 960 selects the target model. Further, in (4) the controller 960 may identify a target model by examining the shape of the model, or by reading the bar code attached to the

target model. In other words, only the essential portion is shown in Fig. 98.

(1) A user directs the controller 960 to a target model.

5 (2) The user touches a touch panel on the controller 960 in order to determine the timing at which the controller 960 transmits to the target model a target model identification signal request signal. Or, the controller 960 is set in advance to transmit a target
10 model identification signal request signal at a predetermined interval.

(3) The controller 960 transmits a target model identification signal request signal to the target model.

15 (4) A target model identification signal is transmitted upon the receipt of the target model identification signal request signal from the controller 960, or according to the setup that a target model identification signal request signal at a
20 specified interval.

(5) The controller 960 that receives the target model identification signal determines a UI in consonance with a target model indicated by the signal, and displays a corresponding UI internally stored. In this
25 case, the identification signal is provided for each model; however, when an identification signal is provided for each device, a different UI can be

employed for each of devices though they are the same model.

Fig. 99 is a flowchart showing the processing performed by the controller 960 when the controller
5 recognizes a target model, and reads and displays a corresponding UI. The processing performed by the controller 960 will now be described.

At step S991 the controller 960 waits until an
instruction from a user is input. At step S992 a
10 target model identification signal request signal is transmitted by an infrared ray communication method in order to obtain a target model identification signal from the target model. At step S993 the controller 960 waits until the target model outputs a target model
15 identification signal. At step S994, the UI corresponding to the received target model identification signal is acquired from internal memory and is displayed.

Fig. 100 is a flowchart showing the processing
20 performed by a target model when the controller 960 recognizes a target model, and reads and displays a corresponding UI. The processing performed by the target model will now be described.

At step S1001, the target model waits for a
25 request signal from the controller 960. At step S1002 the target model transmits a target model identification signal by an infrared communication

2025 RELEASE UNDER E.O. 14176

method, etc.

[Thirty-fifth Embodiment]

Fig. 101 is a diagram showing an example where a controller 960 receives a UI from a target model and displays it. The controller 960, which does not face a target device, has a default screen, as is shown in the center in Fig. 101.

The communication between the controller and the target model will now be described. It should be noted that (2) and (3) are not necessarily required. When, for example, in (4) a target model generates a signal to the controller at predetermined intervals, the same effect can be obtained. The positional relationship between the controller 960 and a target model may be employed to determine that the controller 960 selects the target model. Further, in (4) the controller 960 may identify a target model by examining the shape of the model, or by reading the bar code attached to the target model. In other words, only the essential portion is shown in Fig. 101.

(1) A user directs the controller 960 to a target model.

(2) The user touches a touch panel on the controller 960 in order to determine the timing at which the controller 960 transmits a UI request signal to the target model. Or, the controller 960 is set in advance to transmit a UI request signal at a predetermined

interval.

(3) The controller 960 transmits a UI request signal to the target model.

(4) A UI signal is transmitted upon the receipt of the UI request signal from the controller 960, or according to the setup that a UI request signal at a specified interval.

(5) The controller 960 that receives the UI signal displays the UI.

Fig. 102 is a flowchart showing the processing performed by the controller 960 when the controller receives a UI from a target model and displays it. The processing performed by the controller 960 will now be described.

At step S1021 the controller 960 waits until an instruction from a user is input. At step S1022 a UI request signal is transmitted by an infrared ray communication method in order to obtain a UI signal from the target model. At step S1023 the controller 960 waits until the target model outputs a UI signal. at step S1024, the received UI is displayed.

Fig. 103 is a flowchart showing the processing performed by a target model when the controller 960 receives a UI from a target model and displays it. The processing performed by the target model will now be described.

At step S1031, the target model waits for a

[Thirty-sixth Embodiment]

The controller 960, which does not face a target device, has a default screen, as is shown in the center in Fig. 104.

(1) A user directs the controller 960 to a target model (a copier 962).

(3) The controller 960 transmits controller
25 identification data (controller A) to identify itself
and a UI request signal to the target model.

(4) When the target model receives the controller

identification data and the UI request signal from the controller, the target model transmits, to the server 1041 that manages the target model, the controller identification data (controller A) and target model
5 identification data (copier) to identify itself, and requests the transmission of the UI.

(5) The server 1041 transmits the UI of the target model, which is indicated by the target model data, via a wireless LAN to the controller 960, which is
10 indicated by the controller identification data.

(6) The controller 960 receives the UI addressed to itself, and displays the UI.

Fig. 105 is a flowchart showing the processing performed by the controller 960 when the controller
15 receives a UI via the wireless LAN, instead of directly receiving it from a target model, and displays it.

The processing performed by the controller 960 will now be described. At step S1051 the controller 960 waits until an instruction from a user is input.
20 At step S1052 a UI request signal for requesting a UI and controller identification data for identifying a controller are transmitted to the target model by an infrared ray communication method. At step S1053 the controller 960 waits until a UI signal is output by any
25 device. At step S1054, the received UI is displayed.

Fig. 106 is a flowchart showing the processing performed by the target model when the controller

receives a UI via the wireless LAN, instead of directly receiving it from a target model, and displays it. The processing performed by the controller 960 will now be described.

5 At step S1061 the controller 960 waits until an instruction from a user is input. At step S1062 controller identification data received from the controller 960 and the target model identification data are transmitted to the server 1041, and issuance of the
10 UI is requested.

 Fig. 107 is a flowchart showing the processing performed by the server 1041 when the controller receives a UI via the wireless LAN, instead of directly receiving it from a target model, and displays it. The
15 processing performed by the server 1041 will now be described.

 At step S1071 the server 1041 waits until a UI transmission request signal is transmitted from the target model. At step S1072 the UI of the model, which
20 is indicated by the target model identification data, is transmitted to the controller 960, which is indicated by identification data received from the target model.

[Thirty-seventh Embodiment]

25 Fig. 108 is a diagram showing an example where UIs of devices are stored in a wireless LAN server 1041 and when a controller 960a or 960b faces a facsimile

2025 RELEASE UNDER E.O. 14176

machine 963 as a target model and requests a UI, a different UI for each user is transmitted, upon a request from the facsimile machine 963, from the wireless LAN server 1041 to the controller 960a or 960b, and is displayed.

The controller 960a or 960b, which does not face a target device, has a default screen, as is shown in the center in Fig. 108.

The communication between the user, the controller 960a or 960b and the target model will now be described.

- (1) A user directs the controller 960a or 960b to a target model.
- (2) The user touches a touch panel on the controller 960a or 960b in order to determine the timing at which the controller 960a or 960b transmits a UI request signal to the target model. Or, the controller 960a or 960b is set in advance to transmit a UI request signal at a predetermined interval.
- (3) The controller 960a or 960b transmits controller identification data (controller A or controller B) to identify itself, user identification data (a senior or a beginner) for identifying the user, and a UI request signal to the target model.
- (4) When the target model receives, from the controller 960a or 960b, the controller identification data, the user identification data and the UI request

signal, the target model transmits, to the server 1041 that manages the target model, the received controller identification data, the user identification data and the target model identification data to identify
5 itself.

(5) The server 1041 transmits the UI of the target model, which is indicated by the user identification data and the target model data, via a wireless LAN to the controller 960a or 960b, which is indicated by the
10 controller identification data. In the example in Fig. 108, a UI that is used for multi-address communication, which is difficult for beginners, is transmitted only to seniors, not to beginners.

(6) The controller 960a or 960b receives the UI
15 addressed to itself, and displays the UI.

In the above example, the controller transmits the level data for a user is transmitted as user identification data. However, the controller may transmit information, such as the names of users, to
20 identify individual users, and the target device or the server may identify the level of a user from the received identification data. An independent UI may be prepared for each user.

The above example has been employed only for the
25 UI. The contents of urgent mail addressed to the user or the schedule to be immediately informed are collected in, for example, the server, and they may be

included in the UI while the user identification data that differs among the users is referred to, and the resultant data can be transmitted to the controller.

Fig. 109 is a flowchart showing the processing performed by the controller 960 when the controller receives a different UI for each user, via the wireless LAN, instead of directly receiving it from a target model, and displays it. The processing performed by the controller 960 will now be described.

At step S1091 the controller 960a or 960b waits until an instruction from a user is input. At step S1092 a UI request signal for requesting a UI, controller identification data for identifying a controller, the user identification data for identifying the user are transmitted to the target model by an infrared ray communication method. At step S1093 the controller 960a or 960b waits until a UI signal is output by any device. At step S1094, the received UI is displayed.

Fig. 110 is a flowchart showing the processing performed by the target model when the controller receives a different UI for each user, via the wireless LAN, instead of directly receiving it from a target model, and displays it. The processing performed by the controller 960a or 960b will now be described.

At step S1101 the controller 960a or 960b waits until an instruction from a user is input. At step

S1102 the controller identification data received from the controller 960, the user identification data, and the target model identification data are transmitted to the server 1041, and the issuance of the UI is requested.

Fig. 111 is a flowchart showing the processing performed by the server 1041 when the controller receives a different UI for each user via the wireless LAN, instead of directly receiving it from a target model, and displays it. Fig. 112 is a table showing UIs that are determined by the target model and user identification data. The processing performed by the server 1041 will now be described.

At step S1111 the server 1041 waits until a UI transmission request signal is transmitted from the target model. At step S1112 in accordance with the definitions in Fig. 112, the UI that corresponds to the target model identification data and the user identification data is transmitted to the controller 960a or 960b, which is indicated by identification data received from the target model.

[Thirty-eighth Embodiment]

Figs. 113 and 114 are diagrams illustrating an example where provided is a function that a model to be operated in front does not have. The communication between a user, a controller and a target model will now be described.

(1) A user faces a controller 960 to a target model, and designated a desired function.

(2) The target model receives a request from the controller 960 and transmits it to a server 1041.

5 (3) The server 1041 transmits a UI of a model that corresponds to the requested function.

(4) The controller 960 displays a received UI.

(5) The user performs operation according to an instruction of the UI. In this example, the user sets
10 a document to be transmitted to a copier 962 in front, and the controller 960 instructs the destination to execute the operation.

(6) The target model handles what it can do and requests another apparatus to process what it can not
15 do. In this case, since the copier 962 reads a document but can not facsimile the document, it transmits to a facsimile machine 963 the document data and the contents of the operation instruction.

(7) The facsimile machine 963 transmits by fax the
20 received document data to the instructed destination.

In the above example, to determine an apparatus that the copier 962 asks for the function that the copier 962 can not perform, each apparatus may have knowledge for other apparatuses. Or, the apparatuses
25 on the network may be queried if they can execute the function, and according to the result, the apparatus to be asked for may be determined. Or, an inquiry may be

2025 RELEASE UNDER E.O. 14176

issued to the server 1041 that has knowledge of the models that correspond to functions.

[Thirty-ninth Embodiment]

Fig. 115 is a diagram illustrating an example where, when a controller can not directly communicate with a target model in front because an obstacle is present in route between the target model and the controller, indirect communication is attempted using another route.

The communication between the user, the controller and the target model will now be described. It should be noted that (2) and (3) are not necessarily required. When, for example, in (4) a target model generates a signal to the controller at predetermined intervals, the same effect can be obtained. In other words, only the essential portion is shown in Fig. 115.

(1) A user directs the controller 960 to a target model.

(2) The user touches a touch panel on the controller 960 in order to determine the timing at which the controller 960 transmits a UI request signal to the target model. Or, the controller 960 is set in advance to transmit a UI request signal at a predetermined interval.

(3) The controller 960 transmits a UI request signal to the target model.

(4) A UI signal is transmitted upon the receipt of the

SECRET E066630

(5) The controller 960 that receives the UI signal displays the UI.

(6) If a UI is not transmitted following a predetermined period of time after the UI request signal was transmitted, or if a UI is not transmitted during a period longer than a predetermined interval, which is set for transmission of UIs, another route is employed to transmit a UI request signal. In this example, when infrared communication can not be performed, communication through a wireless LAN is attempted.

(7) The UI acquired across the LAN is displayed.

Fig. 116 is a flowchart showing the processing performed by a controller for an example where, when the controller can not directly communicate with a target model in front because an obstacle is present in route between the target model and the controller, indirect communication is attempted using another route. The processing performed by the controller 960 will now be described.

At step S1161 the controller 960 waits until an instruction from a user is input. At step S1162 a UI request signal for requesting a UI and controller identification data for identifying a controller are

transmitted to the target model by an infrared ray communication method. At step S1163 a check is performed to determine whether or not the UI has been received. At step S1164 a check is performed to
5 determine whether a predetermined period of time has elapsed following the transmission of the request. At step S1165 a UI request signal, for requesting a UI, and controller identification data, for identifying a controller, are transmitted by a route, such as across
10 a wireless LAN, that is different from the route at step S1162. At step S1166 the received UI is displayed.

In this case, the UI request signal that is directly transmitted to the target model is to be sent
15 to the wireless LAN server 1041. However, since the wireless LAN server 1041 that receives the UI request signal is not sure of a target model, first a menu for selecting a model (function) is displayed. A UI corresponding to the selected model is displayed. Upon
20 receipt of the model selection signal from the controller 960, the wireless LAN server 1041 may transmit to the controller 960 a UI that corresponds to the model, or may transmit the menu and a plurality of UIs available from the menu.

25 [Fortieth Embodiment]

Fig. 117 is a diagram showing an example where an operation and an action performed by a user, the time

“SECRET” E2000000

and associated important information are stored as history.

5 An explanation will be given for the processing for storing, as history, the operation/action performed by the user, the time and the associated important information.

(1) A user sets a document in a facsimile machine 963, and instructs the transmission of the document and the user's name (sender's name) to Mr. a of A company.

10 (2) According to the instruction, the facsimile machine 963 transmits the document to Mr. a. Also according to the instruction from Tom, the facsimile machine 963 notifies the server 1041 of the fact that the document has been transmitted to Mr. a together

15 with the transmitted document and the transmission time.

(3) The server 1041 saves the received document as a file "File ABC" and stores the fact of the receipt as history information.

20 Fig. 118 is a flowchart showing the processing performed by the controller for an example where an operation and an action performed by a user, the time and the associated important information are stored as history data. The processing performed by the

25 controller will now be described.

At step S1181 the controller 960 waits until an instruction from a user is input. At step S1182 a

request signal, for the instruction of the user,
controller identification data, for identifying a
controller, and the user identification data, for
identifying the user, are transmitted by an infrared
5 ray communication method. At step S1183 the controller
960 waits until a UI signal is output by any device.
At step S1184, the received UI is displayed.

Fig. 119 is a flowchart showing the processing
performed by the target model for an example where an
10 operation and an action performed by a user, the time
and the associated important information are stored as
history data. The processing performed by the target
model will now be described.

At step S1191 the target model waits until a
15 request signal is transmitted by the controller 960.
At step S1192 a process corresponding to the request
signal from the controller 960 is performed. In the
example shown in Fig. 117 a document set by the user is
read and transmitted to Mr. a of A company. At step
20 S1193 controller identification data received from the
controller 960, the user identification data, and
target model identification data, and important data
associated with the action that was performed, are
transmitted to the server 1401. In the example in Fig.
25 117, according to the instruction from Tom, the fact
that the document was transmitted to Mr. a is sent to
the server 1041, together with the transmission time

and the transmitted document that is the important information associated with the fact.

Fig. 120 is a flowchart showing the processing performed by the server for an example where an operation and an action performed by a user, the time and the associated important information are stored as history data. Fig. 121 is a diagram showing example history information that is updated as the result of processing. The processing performed by the server will now be described.

At step S1201 the server waits until it receives a request signal from the target model. At step S1202 the important information associated with the received fact is stored. In the example in Fig. 117 the document the transmission of which is instructed by Tom is saved as File ABC.

At step S1203 the history data are updated in consonance with the received fact. In the example shown in Fig. 117 the fact that Tom transmitted a document to M. a of A company at 10:00 on July 5, 1996 is recorded together with the file name stored at step S1201. Fig. 121 is a table showing updated history data; the fact that Mary printed ten copies of File XYZ on July 3, 1996, and the fact that Tom transmitted File ABC to Mr. a of A company at 10:00 on July 5, 1996. At step S1204 a UI that indicates the normal termination of the processing is transmitted to the controller that

2025 RELEASE UNDER E.O. 14176

[Forty-first Embodiment]

5

10

15

(2) Upon receipt of the instruction, the copier 962

20

25

(7) The copier 962 prints a document received by the server 1041.

In the above example, the fact "File ABC was sent to Mr. a of A company" is selected from the history in order to acquire necessary material from the copier 962 in front. When the name of document "File ABC" to be output is obtained, the list of files can be displayed instead of the history data and the file name can be selected, or the file name can be input directly.

In addition, in the above example, the document to be extracted is the one that is transmitted by the facsimile machine 963 and stored in the server 1041. A document stored in a PC across the network can also be employed.

Fig. 124 is a diagram showing the structure of the controller 960 used in this embodiment.

A display 1241 is used to display data on a liquid crystal screen. A resistance film is attached to the display 1241, and data can be input with a pen 1242. A button on a screen may be selected by the pen 1242. Furthermore, a character recognition function is

provided, and the characters written with the pen 1242 can be input. Instead of this function, a voice input/recognition function may be employed to input information.

5 The input information can be transmitted from a communication unit 1243 to another apparatus. A CPU 1244 for controlling and a storage unit 1245 are provided inside the apparatus, and input information and information received by the communication unit 1243
10 and the history of the operations are stored. The storage unit 1245 can be a SRAM card, an SIMM or an HDD. The controller 960 is battery operated and water resistant.

 Fig. 125 is a diagram illustrating another example
15 structure of the controller 960 used in the embodiment.

 A display 1251 is used to display data using liquid crystal or a CRT. A touch panel can be additionally provided as an option to the display 1251. Thus, information can be input by a finger or a pen.
20 An input unit 1252 is used to input information by manipulation of a button. The input data can be transmitted from a communication unit 1253 to another apparatus. A CPU 1254 for controlling and a storage unit 1255 are provided inside the apparatus, and input
25 information and information received by the communication unit 1253 and the history of the operations are stored. The storage unit 1255 can be a

SRAM card, an SIMM or an HDD.

The controller in Fig. 125 can be used as a button
controller with the storage unit 1255 being removed.
The controller can be used as a personal digital
5 assistant (PC) with the communication unit 1253 being
removed. In addition, the controller can be used as is
shown in Fig. 124, with the input unit 1252 being
removed and with the touch panel provided.

Fig. 126 is a diagram showing an additional
10 example structure of the controller 960 used in this
embodiment.

A display 1261 is used to display data using
liquid crystal. An input unit 1262 is used to input
information by manipulating a button. The input data
15 can be transmitted by an infrared communication unit
1263 to another apparatus. A CPU 1264 for controlling
and a storage unit 1265 are provided inside the
apparatus, and input information and information
received by the infrared communication unit 1263 and
20 the history of the operations are stored. The storage
unit 1265 can be a SRAM card, an SIMM or an HDD.
Furthermore, a PCMCIA slot 1266 is provided, and, for
example, a PCMCIA card is loaded into the slot 1266 to
enable the connection by a PCMCIA bus, so that two
25 communication channels can be employed. The infrared
communication unit 1263 may be used only for
transmission by light emission, and the PCMCIA bus may

be used for reception. Of course, the connection by the PCMCIA bus may not be employed.

[Forty-second Embodiment]

5 This system arrangement according to this embodiment is as shown in Figs. 41A and 41B, and information processing apparatuses 411, 412 and 413 can communicate with each other.

10 When the information processing apparatus 411 needs information stored in the information processing apparatus 412, or when the information is to be transmitted to the information processing apparatus, or when an instruction is to be transmitted to the information processing apparatus 412, the information processing apparatus 411 requests the communication
15 with the information processing apparatus 412 and exchanges required information and an instruction.

Any apparatus can be used for the information processing apparatuses 411, 412 or 413 so long as they have necessary communication function; a printer, a
20 scanner, a facsimile machine, a desktop PC or a digital camera can be used.

Fig. 127 is a diagram illustrating the functional arrangement for this embodiment.

25 An operating unit 41 displays a screen required for a user to operate in accordance with data stored in an operation data memory area 42. An operation performed by a user or an instruction issued by a user

is acquired by the operation unit 41 and transmitted to a task reception unit 43.

The operation data 42 is data to be referred to by the operation unit 41, and specifies the process at the operation unit 41. In this embodiment, based on the information received by the task reception unit 43, the operation data 42 is altered or updated by a process execution unit 47, which will be described later, so that flexible procedures can be provided.

One of methods for operating an apparatus other than the information processing unit 411, i.e., the information processing apparatus 412, is the one for acquiring the operation data 42 for the information processing apparatus 412 and for altering and updating the operation data 42 of the information processing apparatus 411.

In another example, the presence of the information processing apparatus 412, which is connected across the network to the information processing apparatus 411 in this embodiment, is detected, so that a new function obtained by combining the two information processing apparatuses can be implemented. Information required for an instruction for the function is added to the operation data 42, and thus, the function obtained by combining a plurality of apparatuses can be provided.

The task reception unit 43 receives not only

information from the operation unit 41, but also receives, as the status change, a change in the environment of the information processing apparatus 411 or a task received from another apparatus, such as the information processing apparatus 412. Task reception unit 43 also detects the connection of a new information processing apparatus to the network, receives as a task a print instruction from another apparatus, or detects that no process is performed during a specified period of time. As a result, received information is added as a new task to a task table 44.

The task reception unit 43 is required as well as the process execution unit 47, which will be described later, to communicate with different apparatuses.

The task table 44 is a table in which are stored tasks having the activation condition and the contents. Figs. 129A to 129F are examples for the task table 44.

In Figs. 129A to 129F, the tasks are stored from the top of the table in the order of priorities. The addition of a task to the task table 44 is performed by the previously mentioned task reception unit 43 and the process execution unit 47 to be described later. Extraction of the task from the task table 44 is performed by a task analysis unit 45, which will be described later.

The task analysis unit 45 extracts a task having

the highest priority from the task table 44, and analyzes the object of the task. Since the task analysis unit 45 analyzes the object, a planning decision unit 46 and the process execution unit 47 can avoid inefficient processing and can perform an optimal process.

For example, a task 63 in the task table 44 in Figs. 129A to 129F is analyzed and understood that the direct object is printing and the final object is to transmit a printed document to a user. If the final object can be achieved by an efficient method, it is found that even printing is unnecessary, and planning is performed according to that effect. The information to be processed is also analyzed, and it is found that format conversion is required.

The planning decision unit 46 receives the analysis from the task analysis unit 45, makes planning for a process to be performed. For example, for the task 63 stored in the task table 44 in Figs. 129A to 129F, a process for extracting an object from an apparatus B before printing of the object is planned.

The process execution unit 47 performs a process according to the contents determined by the planning decision unit 46, e.g., sends an instruction to another apparatus. The process execution unit 47 will be described in detail in a forty-third embodiment and following embodiments. The functional arrangement in

Fig. 127 can be provided by the hardware configuration in Fig. 3.

Fig. 128 is a flowchart showing the processing for this embodiment.

5 When the information processing apparatus 411 in this embodiment is activated, at step S51 the task table 44 is initialized as is denoted by 61 in Fig. 129A.

10 Then, at step S52 a check is performed to determine whether the task reception unit 43 has received, as the status change, information that is acquired by the operation unit 41 for an operation instruction from a user, an environmental change, or a task from another apparatus. When the task is
15 received, program control advances to step S53, and as is shown in Fig. 129B, the analysis task 62 of the received information is added to the head of the task table 44.

20 Following this, at step S54 a check is performed to determine whether or not an executable task is present in the task table 44. If there is no such task, program control returns to step S52, whereat the reception of the task is examined again. If there is such a task, program control moves to step S55, whereat
25 the task having the highest priority is extracted from the task table 44.

At step S56 the object of the task is analyzed,

and at step S57 the process to be performed is planned and decided. If the task table is in the state shown in Fig. 129B, highest priority task 62 "ANALYZE" is extracted, it is apprehended that its object is analysis of received information, and planning for analysis is performed.

At step S58 the process according to the planning is performed, and as needed, a new task is added to the task table 44. When, for example, the received information is analyzed according to the plan obtained from the task 62 "ANALYZE" in Fig. 129B, the contents "Print 'contract.doc' from B" which is instructed by a user through the operation unit 41, are analyzed and a new task 63 "PRINT" is added as is shown in Fig. 129C.

Program control returns again to step S52. However, since no new task is received, program control moves to step S54, and the above process is repeated. As a result, task 63 "PRINT" in Fig. 129C, which was added at step S58, is extracted, analyzed and planned. To execute task PRINT, it is found that the object must be present in the information processing apparatus 411, and new task 64 "PULL" and task 65 "PRINT" which employs the "pulled" object, are added as is shown in Fig. 129D.

In addition, when the processing is repeated, the task 64 "PULL" in Fig. 129D is executed. Since the contents of the task PULL are important portions for

the present invention, detailed explanation for them will be given for the forty-third embodiment and the following.

When the process is further repeated, the object
5 that is acquired as the result of the task PULL is employed to perform task 65 in Fig. 129E. As a result, the task table 44 is returned to the initial state, as is shown in Fig. 129F.

[Forty-third Embodiment]

10 Fig. 130 is a diagram showing an example input/output device that can operate another apparatus.

The operation procedure (UI) implemented by the operation unit 41 is performed by referring to the operation data 42 that the information processing
15 apparatus 411 originally includes, or by referring to the operation data 42 that is acquired from another information processing apparatus 412 connected to the network.

An instruction 71 by a user's voice, or the
20 employment of an operation panel screen 72 to designate a target device, is performed by referring to the operation data 42 that are originally included in a copier, which serves as the information processing apparatus 411.

25 The copier 74, which is the information processing apparatus 411, executes the task PULL at the process execution unit 47, and refers to on the operation data

44166737 "FEB 66 66"

42, which are acquired from a facsimile machine 75 that serves as the information processing apparatus 412 connected via the network, to designate a transfer destination and a condition by using the screen 73 of the operation panel.

The operation data 42 of the facsimile machine 75 may be held by the copier 74 in advance, and be referred to as needed.

The operation data 42 of the facsimile machine 75 may be acquired from another device, such as a server.

A specific method for communication between the information processing apparatuses 411 and 412 will be explained in detail for a forty-ninth embodiment and the following embodiments.

[Forty-fourth Embodiment]

Fig. 131 is a diagram showing an input/output apparatus that can operate a function obtained by a combination of a plurality of devices.

The procedure (UI: User Interface) implemented by the operation unit 41 is performed by referring to the operation data 42 the information processing apparatus 411 originally includes, or by referring to the operation data 42 that is updated as the result of the detection of the information processing apparatus 412 connected via the network.

The number of copies using the operation panel 81 in Fig. 131 is designated by referring to the operation

data 42 that is originally included in the copier 74,
which serves as the information processing apparatus
411. The "Copy" displayed in the lower portion of the
operation panel indicates an instruction of copying,
5 and "transmit" displayed in the hatched state indicates
that the transmission process is disabled.

As the result of the detection of the facsimile
machine 75, which serves as the information processing
apparatus 412 connected via the network, the operation
10 data 42 of the copier 74 are updated to the function
that can be used, i.e., the transmission function from
which the hatching is removed, and is referred to, so
that the number of copies on a display 82 is designated
using the operation panel, as well as the operation
15 panel 81.

When a user selects and instructs the execution of
the transmission function, a display 83 for designating
the transmission destination is provided and the
transmission function can be executed. As is described
20 above, when a user need only set a desired document on
a copier near the user and instruct the execution of
the transmission function, the document can be
transmitted by using the function of the facsimile
machine 75, which is at a remote area and is connected
25 via a network. This accomplishes both the document
input function of the copier and the document
transmission function of the facsimile machine.

When the facsimile machine 75 is not connected on the display 81, the transmission operation on the display 83 for designating the transmission destination is performed in advance, and at the same time that the connection of the facsimile machine 75 is detected, the contents of the transmission operation is transmitted to the facsimile machine 75. Thus, in consonance with the contents, the automatic transmission can be performed, or the reservation operation, such as a confirmation to a user before automatic transmission, as is shown in a screen 84, can be performed.

In this embodiment, while the facsimile machine 75 is not connected, the display "transmit" for a transmission instruction is displayed by hatching to indicate transmission is enabled. Such a display may not be provided at all.

A specific method for communication between the information processing apparatuses 411 and 412 will be described in detail for the forty-ninth embodiment and the following.

[Forty-fifth Embodiment]

Fig. 132 is a diagram illustrating an example input/output device that can communicate with a user.

In the example in Fig. 132, a user sends an instruction 93 to a copier 91 that is physically located in a remote area in order to permit a MyDesk 92, a desktop personal computer, to display the current

location of the user.

The instruction 93 "Display present place on
<MyDesk>", which is sent to the copier 91 that serves
as the information processing apparatus 411, is
5 transmitted from the operation unit 41 to the task
reception unit 43. The contents are analyzed and
planning is performed on the results. Then, the
execution unit 47 executes the final data as an
instruction task INDICATE for a PC 92, which serves as
10 the information processing apparatus 412 connected via
the network.

The PC 92, which is the information processing
apparatus 412 connected via the network, receives
communication task COMMUNICATION from the reception
15 unit 43, analyzes a received instruction, and perform
planning on the results. Then, the execution unit 47
displays a message on a screen.

A specific method for communication between the
information processing apparatuses 411 and 412 will be
20 described in detail for the forty-ninth embodiment and
the following.

[Forty-sixth Embodiment]

Fig. 133 is a diagram illustrating an example
input/output device that can acquire information from
25 another apparatus.

In the example in Fig. 133, a user sends an
instruction 1333 to a printer 1331 that is located in a

"contract.doc" that is stored in apparatus B1332.

5

10

15

20

[Forty-seventh Embodiment]

Fig. 134 is a diagram illustrating an example

input/output device that can be stored in another apparatus.

In the example shown in Fig. 134, a user reads a document 115 using a scanner 111 and sends an
5 instruction 113 to permit a filing server 112 at a physically remote area to perform filing with a title and an index.

The instruction 113 "Filing to Filing Server, Title, Index Extraction" which the user sent to the
10 scanner 111 that serves as the information processing apparatus 411, is transmitted from the operation unit 41 to the task reception unit 43. The contents are analyzed and planning is performed on the results. Then, the execution unit 47 executes the final data as
15 information storage task PUSH for the filing server 112, which serves as the information processing apparatus 412 connected via the network.

The filing server 112, which serves as the information processing apparatus 412 connected via the
20 network, receives the information storage task PUSH from the reception unit 43, analyzes the received instruction, and performs planning on the data. The execution unit 47 then files corresponding information 115 "contract.doc".

25 A specific method for communication between the information processing apparatuses 411 and 412 will be described in detail for the forty-ninth embodiment and

the following.

[Forty-eighth Embodiment]

Fig. 135 is a diagram illustrating an example
input/output device that can be stored in another
5 apparatus.

In the example shown in Fig. 135, a user sends an
instruction 123 to a printer 121 to transmit
information 125, which is stored in a filing server 122
located at a physically remote area, to John 124 who is
10 located at a physically farther area.

The instruction 123 "Action: SEND, What: abc.doc,
From: Filing Server, To: John" which the user sent to
the printer 121 that serves as the information
processing apparatus 411, is transmitted from the
15 operation unit 41 to the task reception unit 43. The
contents are analyzed and planning is performed on the
results. Then, the execution unit 47 executes the
final data as an instruction task for the filing server
122, which serves as the information processing
20 apparatus 412 connected via the network.

The filing server 122, which serves as the
information processing apparatus 412 connected via the
network, receives the instruction task from the
reception unit 43, analyzes the received instruction,
25 and performs planning on the data. The execution unit
47 then transmits corresponding information 125
"abc.doc" to John by E-mail.

A specific method for communication between the information processing apparatuses 411 and 412 will be described in detail for the forty-ninth embodiment and the following.

5 [Forty-ninth Embodiment]

Figs. 136A and 136B are flowcharts showing the processing for <COMMUNICATE> task.

<COMMUNICATE> task is performed when arbitrary apparatuses A and B need communicate with each other.
10 In Figs. 136A and 136B are shown the processing that the apparatus A (a source) that transmits a COMMUNICATE request is to execute for communication with the apparatus B (destination) that receives a COMMUNICATE request.

15 At step S1312, the apparatus A contacts the apparatus B to establish the connection for communication. At step S1313 a check is performed to determine where a reply is received from the apparatus B. If there is no response from the apparatus B, at
20 step S1314 a check is performed to determine whether or not a user or another person should be notified of no response. If notification is necessary, at step S1315 a notification is issued to a user by an appropriate means/medium. At step S1316, according to the
25 decision/assumption of the system or the setup by the user, a check is performed to determine whether the task should be re-execute by the system later. If the

re-execution of the task is necessary, at step S1317 the task is added to the task table, and the processing is thereafter terminated. If the re-execution of the task is not required, at step S1318 the task is
5 deleted, and is added to "failed list". The processing is thereafter terminated.

When, at step S1313, a response is received, at step S1319 whether the response is "Will call back" is determined. If the response is "Will call back" the
10 apparatus B will call back the apparatus A later. At step S1320, a check is performed to determine whether or not the user or another person should be notified of the response. If notification is necessary, at step S1321 the notification is issued to the user by an
15 appropriate means/medium. At step S1322 the system adds the task to the task table, and remembers that the apparatus B will call back so as to cope with the call back. The processing is thereafter terminated.

If, at step S1319, the response is not "Will call
20 back" at step S1323 whether the response is "Contact later" is determined. If the response is "Contact later" it is assumed that the apparatus B wants a contact later, and the above described processes at step S1314 and the following steps are performed.
25 When, at step S1323, the response is not "Contact later" it is assumed that the response is "OK" and at step S1324 the response is confirmed. If the response

is not "OK" an error occurs. At step S1331 an error message is displayed.

When the response is "OK" at step S1325 a check is performed to determine whether or not a negotiation
5 with the apparatus B is required for the current operation. If the negotiation is required, at step S1326 a negotiation is initiated. The object to be negotiated includes a data format for data execute and protocol/version exchange, and a data format for other
10 information required in advance for correct communication. This negotiation is repeated until the communication base used in common for the apparatuses A and B is established.

At step S1327 information to be transmitted is
15 issued as an request from the apparatus A to the apparatus B. At step S1328, whether or not a response is received. When the response is received, at step S1329 a check is performed to determine whether there is an action to be executed relative to the received
20 response. The action is, for example, conversion of a format or erasure of an unnecessary header. The object of the communication includes actions such as printing, transmission, filing, voice output and display. This means that necessary actions should be executed, and at
25 step S1330 these actions are added to the task table.

When, at step S1328, there is no response, the above described processes at step S1314 and the

following steps are performed. The above processing loop is continued until requested information is obtained or until the system can not continue the processing.

5 [Fiftieth Embodiment]

Figs. 137A and 137B are flowcharts showing the processing for <PULL> task.

10 <PULL> task is performed when an arbitrary apparatus A needs to extract information from an apparatus B. In Figs. 137A and 137B are shown the processing that the apparatus A (a source) that transmits a PULL request is to execute for communication with the apparatus B (destination) that receives a PULL request.

15 At step S1412, the apparatus A contacts the apparatus B to establish the connection for communication. At step S1413 a check is performed to determine where a reply is received from the apparatus B. If there is no response from the apparatus B, at
20 step S1414 a check is performed to determine whether or not a user or another person should be notified of no response. If notification is necessary, at step S1415 a notification is issued to a user by an appropriate means/medium. At step S1416, according to the
25 decision/assumption of the system or the setup by the user, a check is performed to determine whether the task should be re-execute by the system later. If the

re-execution of the task is necessary, at step S1417 the task is added to the task table, and the processing is thereafter terminated. If the re-execution of the task is not required, at step S1418 the task is
5 deleted, and is added to "failed list". The processing is thereafter terminated.

When, at step S1413, a response is received, at step S1419 whether the response is "Will call back" is determined. If the response is "Will call back" the
10 apparatus B will call back the apparatus A later. At step S1420, a check is performed to determine whether or not the user or another person should be notified of the response. If notification is necessary, at step S1421 the notification is issued to the user by an
15 appropriate means/medium. At step S1422 the system adds the task to the task table, and remembers that the apparatus B will call back so as to cope with the call back. The processing is thereafter terminated.

If, at step S1419, the response is not "Will call
20 back" at step S1423 whether the response is "Contact later" is determined. If the response is "Contact later" it is assumed that the apparatus B wants a contact later, and the above described processes at step S1414 and the following steps are performed.
25 When, at step S1423, the response is not "Contact later" it is assumed that the response is "OK" and at step S1424 the response is confirmed. If the response

is not "OK" an error occurs. At step S1431 an error message is displayed.

When the response is "OK" at step S1425 a check is performed to determine whether or not a negotiation
5 with the apparatus B is required for the current operation. If the negotiation is required, at step S1426 a negotiation is initiated. The object to be negotiated includes a data format for data execute and protocol/version exchange, and a data format for other
10 information required in advance for correct communication. This negotiation is repeated until the communication base used in common for the apparatuses A and B is established.

At step S1427 information to be extracted is
15 issued as a request from the apparatus A to the apparatus B. At step S1428, whether or not requested information is received. When the requested information is received, at step S1429 a check is performed to determine whether there is an action to be
20 executed relative to the received response. The action is, for example, conversion of a format or erasure of an unnecessary header. The object of the extraction of information includes actions such as printing, transmission, filing, voice output and display. This
25 means that necessary actions should be executed, and at step S1430 these actions are added to the task table.

When, at step S1428, requested information is not

2025 RELEASE UNDER E.O. 14176

acquired, the above described processes at step S1414 and the following steps are performed. The above processing loop is continued until requested information is obtained or until the system can not
5 continue the processing.

[Fifty-first Embodiment]

Figs. 138A and 138B are flowcharts showing the processing for <PUSH> task.

<PUSH> task is performed when an arbitrary
10 apparatus A need to transmit information to an apparatus B. In Figs. 138A and 138B are shown the processing that the apparatus A (a source) that transmits a PUSH request is to execute for communication with the apparatus B (destination) that
15 receives a PUSH request.

At step S1512, the apparatus A contacts the apparatus B to establish the connection for communication. At step S1513 a check is performed to determine where a reply is received from the apparatus
20 B. If there is no response from the apparatus B, at step S1514 a check is performed to determine whether or not a user or another person should be notified of no response. If notification is necessary, at step S1515 a notification is issued to a user by an appropriate
25 means/medium. At step S1516, according to the decision/assumption of the system or the setup by the user, a check is performed to determine whether the

task should be re-execute by the system later. If the re-execution of the task is necessary, at step S1517 the task is added to the task table, and the processing is thereafter terminated. If the re-execution of the task is not required, at step S1518 the task is deleted, and is added to "failed list". The processing is thereafter terminated.

When, at step S1513, a response is received, at step S1519 whether the response is "Will call back" is determined. If the response is "Will call back" the apparatus B will call back the apparatus A later. At step S1520, a check is performed to determine whether or not the user or another person should be notified of the response. If notification is necessary, at step S1521 the notification is issued to the user by an appropriate means/medium. At step S1522 the system adds the task to the task table, and remembers that the apparatus B will call back so as to cope with the call back. The processing is thereafter terminated.

If, at step S1519, the response is not "Will call back" at step S1523 whether the response is "Contact later" is determined. If the response is "Contact later" it is assumed that the apparatus B wants a contact later, and the above described processes at step S1514 and the following steps are performed. When, at step S1523, the response is not "Contact later" it is assumed that the response is "OK" and at

step S1524 the response is confirmed. If the response is not "OK" an error occurs. At step S1531 an error message is displayed.

When the response is 'OK" at step S1525 a check is
5 performed to determine whether or not a negotiation with the apparatus B is required for the current operation. If the negotiation is required, at step S1526 a negotiation is initiated. The object to be
10 negotiated includes a data format for data execute and protocol/version exchange, and a data format for other information required in advance for correct communication. This negotiation is repeated until the communication base used in common for the apparatuses A and B is established.

15 At step S1527 information to be transmitted is issued as a request from the apparatus A to the apparatus B. At step S1528, whether or not a response is received. When the response is received, at step S1529 a check is performed to determine whether there
20 is an action to be executed relative to the received response. The action is, for example, conversion of a format or erasure of an unnecessary header. The object of the communication includes actions such as printing, transmission, filing, voice output and display. This
25 means that necessary actions should be executed, and at step S1530 these actions are added to the task table.

When, at step S1528, there is no response, the

above described processes at step S1514 and the following steps are performed. The above processing loop is continued until requested information is obtained or until the system can not continue the processing.

[Fifty-second Embodiment]

Figs. 139A and 139B are flowcharts showing the processing for <INDICATE> task.

<INDICATE> task is performed when an arbitrary apparatus A needs to send an instruction to an apparatus B. In Figs. 139A and 139B are shown the processing that the apparatus A (a source) that transmits an INDICATE request is to execute for communication with the apparatus B (destination) that receives an INDICATE request.

At step S1612, the apparatus A contacts the apparatus B to establish the connection for communication. At step S1613 a check is performed to determine where a reply is received from the apparatus B. If there is no response from the apparatus B, at step S1614 a check is performed to determine whether or not a user or another person should be notified of no response. If notification is necessary, at step S1615 a notification is issued to a user by an appropriate means/medium. At step S1616, according to the decision/assumption of the system or the setup by the user, a check is performed to determine whether the

5

10

20

25

step S1624 the response is confirmed. If the response is not "OK" an error occurs. At step S1631 an error message is displayed.

When the response is 'OK" at step S1625 a check is
5 performed to determine whether or not a negotiation with the apparatus B is required for the current operation. If the negotiation is required, at step S1626 a negotiation is initiated. The object to be
10 negotiated includes a data format for data execute and protocol/version exchange, and a data format for other information required in advance for correct communication. This negotiation is repeated until the communication base used in common for the apparatuses A and B is established.

15 At step S1627 according to the operation instruction by the user employing the operation unit 41, an instruction is issued as an request from the apparatus A to the apparatus B. At step S1628, a check is performed to determine whether or not a response is
20 received. When the response is received, at step S1629 a check is performed to determine whether there is an action to be executed relative to the received response. The action is, for example, conversion of a format or erasure of an unnecessary header. The object
25 of the communication includes actions such as printing, transmission, filing, voice output and display. This means that necessary actions should be executed, and at

step S1630 these actions are added to the task table.

When, at step S1628, there is no response, the above described processes at step S1614 and the following steps are performed. The above processing loop is continued until requested information is obtained or until the system can not continue the processing.

[Fifty-third Embodiment]

Figs. 140A and 140B are flowcharts showing the processing for <RESPOND> task.

<RESPOND> task is performed when an apparatus B (destination) that receives a COMMUNICATE request sends a response. In Figs. 140A and 140B are shown the processing that is to be executed by the apparatus B that receives a COMMUNICATE request (e.g., PULL) from a transmission apparatus (source) A.

At step S1712 a check is performed to determine whether or not a request type is contact. If the request is contact, the apparatus A attempts to establish connection with the apparatus B for communication. At step S1713 the current status or a specific user's set value is allocated for status S1. At step S1314 whether the status S1 is a "Very busy" mode or a "Standby" mode is determined. If the status S1 is either mode, it is assumed that the apparatus B can not accept the request from the apparatus A. Then, at step S1715 the optimal response is decided. A check

is performed to determine whether or not the apparatus B can call back the apparatus A any time. If the apparatus B can call back, program control moves to step S1716 and response "Will call back" is
5 transmitted. If the apparatus B can not call back, at step S1717 response "Contact later" is transmitted. This means that the apparatus A must contact the apparatus B later. When, at step S1714, the status A1 is neither a "Very busy" mode nor a "Standby" mode,
10 response "OK" is transmitted. The processing is thereafter terminated.

When the request type is not contact, at step S1719 a check is performed to determine whether the request type is a request for information. If so, at
15 step S1720 a response is transmitted relative to the request for information, which will be described later in Fig. 141. When the request type is not a request for information, at step S1721 a check is performed to determine whether the request type is a request for
20 storage of information. If so, at step S1722 a response relative to the request for storage of information, which will be described later in Fig. 142, is issued. If the request type is not a request for storage of information, at step S1723 a check is
25 performed to determine whether the request type is a request for an instruction. If so, at step S1724 a response relative to the request for an instruction,

which will be described later, is issued. If the request type is not a request for an instruction, at step S1725 an optimal response is issued, and the processing is thereafter terminated.

5 Fig. 141 is a flowchart showing a response task relative to the request for information. In this flowchart, a process will be explained that is initiated when the request type is a request for information (step S1720 in Figs. 140A and 140B).

10 At step S1812 a check is performed to determine whether or not negotiation is required with the apparatus A that issued the request for an instruction. If the negotiation is required, program control moves to step S1813, whereat the negotiation is initiated.

15 The object to be negotiated includes a data format for data execute and protocol/version exchange, and a data format for other information required in advance for correct communication. This negotiation is repeated until the communication base used in common for the

20 apparatuses A and B is established.

 Following this, at step S1814 fetching of requested information is performed. At step S1815, a check is performed to determine whether or not the requested information is found. If the information is

25 not found, at step S1816 response = NG is transmitted and the processing is terminated.

 If the requested information is found, at step

S1817 a check is performed to determine whether the information should be transferred immediately. If the immediate transmission is required, program control moves to step S1820, whereat a check is performed to
5 determine whether or not data formatting or data conversion is required. If data formatting or data conversion is required, at step S1819 it is performed. Then, at step S1820 the requested information is transmitted as a response and the processing is
10 thereafter terminated. If the immediate transmission is not required, program control moves to step S1821, whereat a task for transmitting the data later is added to the task table. At step S1822 response = OK is issued, and the processing is terminated.

15 Fig. 142 is a flowchart showing a response task relative to the request for storage of information. In this flowchart, a process will be explained that is initiated when the request type is a request for storage of information (step S1722 in Figs. 140A and
20 140B).

At step S1912 a check is performed to determine whether or not negotiation is required with the apparatus A that issued the request for an instruction. If the negotiation is required, program control moves
25 to step S2013, whereat the negotiation is initiated. The object to be negotiated includes a data format for data execute and protocol/version exchange, and a data

format for other information required in advance for correct communication. This negotiation is repeated until the communication base used in common for the apparatuses A and B is established.

5 Following this, at step S1914 information transmitted for the apparatus A is acquired. At step S1915 whether or not the information is received is determined. If the information is not yet received, program control goes to step S1916, whereat response =
10 NG is returned, and the processing is terminated. If the information received, whereat a check is performed to determine whether or not data formatting or data conversion is required. If data formatting or data conversion is required, at step S1918 it is performed.
15 Then, at step S1919 response = OK is issued, and the processing is terminated.

Fig. 143 is a flowchart showing a response task relative to a request for an instruction. In this flowchart, a process will be explained that is
20 initiated when the request type is a request for an instruction (step S1724 in Figs. 140A and 140B).

At step S2012 a check is performed to determine whether or not negotiation is required with the apparatus A that issued the request for an instruction.
25 If the negotiation is required, program control moves to step S1913, whereat the negotiation is initiated. The object to be negotiated includes a data format,

conversion protocol, upgrading of a version,
adjustments associated with alteration of information
types, and specification of the instruction contents.
The negotiation process is planed before this process
5 is initiated.

Following this, at step S2014 instruction
information is interpreted to decide a process to be
performed next. At step S2015 a check is performed to
determine whether or not the process can be executed.
10 If the process can not be performed, response = NG is
returned and the processing is terminated.

When the process can be performed, program control
moves to step S2017, whereat whether or not immediate
execution is required. If the process need not be
15 performed immediately, program control goes to step
S2020, whereat a task for designating the performance
of a corresponding process is added to the task table,
and response = OK is returned. The processing is
thereafter terminated.

20 If the process should be immediately performed,
program control advances to step S2018, whereat the
instructed process is performed. The processing is
thereafter terminated.

[Fifty-fourth Embodiment]

25 An explanation of PULL task, for example pull
printing for extracting and printing information, i.e.,
an example print on demand process will now be given,

by referring to Fig. 133.

In the example in Fig. 133, a user sends an instruction 1333 to a printer A1331 to extract information 1334 "contract.doc" included in an
5 apparatus B1332 that is located physically away from the printer A and to permit the printer A to print the information 1334. The apparatus B can be a printer, a scanner, a desktop PC, or a filing server.

The contents "Please fetch 'contract.doc' from B
10 and print it" which is an instruction from the user to the printer A1331, may be a command input using a mouse, or via a keyboard, by voice or a digitizer, or may be a sentence in the natural language by character recognition.

15 When the apparatus B is a different device type from the apparatus A, e.g., a scanner, the information formatting is TIFF, BMP or JPEG, and format conversion is required. This data conversion may be performed either by the apparatus B or by the printer A to obtain
20 the appropriate data format. When the apparatus B is a printer and information of the apparatus B has a format that the printer A can understand (e.g., when both apparatuses A and B are PCL printers), data conversion is not required. In other cases, even when both
25 apparatuses are printers, data conversion is necessary. It should be noted that the apparatus A is not necessary a printer, and may be another output device,

such as a facsimile machine, a copier or a display.

The transmission of information for the PULL task will now be described. Fig. 144 is a diagram showing an example pull session. In this example, the
5 apparatuses A and B are printers, but as is described above, the apparatuses A and B need not necessarily be the same device type, and can be a scanner, a printer, a copier or a facsimile machine.

The apparatus A performs the procedures in Figs.
10 137A and 137B while the apparatus B performs the procedures in Fig. 141. First, the apparatus A contacts the apparatus B to establish a connection for communication (step S1412). When the response is OK (steps S1424 and S1822), a request for information
15 (information <abc> in this example) and an information format, if necessary, are transmitted to the apparatus B (step S1427).

The apparatus B fetches the requested information (step S1814), converts the format, as needed (step
20 S1819), and transmits information in response to the request (step S1820).

When the apparatus A extracts information from the apparatus B, it executes a necessary action in accordance with the instruction from the user or the
25 determination of the system. The necessary action is, for example, printing, and in this case, pull printing is performed, i.e., information is extracted from a

remote area and printed. In other words, print on demand can be accomplished.

Another necessary action is a display. In this case, pull viewing is performed, i.e., information is
5 extracted from a remote area and displayed. In other words, view on demand can be accomplished. An additional necessary action is audio output. In this case, pull hearing is performed, i.e., information is extracted from a remote area and can be listened to.
10 In other words, hear on demand can be accomplished.

Similarly, further necessary actions are storage, filing and transferring. Any type of information can be extracted; a document, a file, electronic mail, a schedule, a status report, a log, voice mail or
15 telephone call.

[Fifty-fifth Embodiment]

Fig. 145 is a diagram showing another example pull session. Along the same procedure as in Fig. 144, the apparatus A requests information <abc> to the apparatus
20 B. However, the apparatus B does not immediately transmits the requested information (No at step S1817). A task for transmitting the data later is added to the task table (step S1821), and response = OK is returned to terminate the processing (step S1822). In this
25 case, the transfer of the requested information is a print request from the apparatus B after a new session is established.

[Fifty-sixth Embodiment]

Fig. 146 is a diagram showing an additional example pull session. In this example, a negotiation is held before the transfer of necessary information (steps S1425 and S1426 and steps S1812 to S1822). Since the information to be extracted by the apparatus A is a file, the apparatus A requests the apparatus B for a list of files. The apparatus B transmits the list of files to the apparatus A. From the list, the apparatus decides information necessary for the system or instructs the input of information necessary for a user. The apparatus A then decides the information to be requested, and issues a request for information to the apparatus B in the same manner as described above.

[Fifty-seventh Embodiment]

Fig. 147 is a diagram showing an example of Hear On Demand. In this example, "Read out New Mail" is input. While, in Fig. 147, an input window is employed for this input, any input device, such as a voice input device, a keyboard or a digitizer, can be employed as in the previous examples.

In this example, the above command is transmitted to an apparatus A (printer) at Kosugi, and mail to be output is stored in an apparatus B (desktop PC) at Shimomaruko. The apparatuses A and B may be located in the same place, or in the same or different network domain. This session will be described while referring

to Fig. 148.

Fig. 148 is a diagram showing a further example pull session. Information type is electronic mail and a requested format is voice. The procedures are,
5 however, the same as previously described.

The apparatus A requests the information (mail) (step S1427), the apparatus B converts the requested data into a suitable format (voice format in this example) (step S1819), and sends a response. Then, the
10 apparatus A performs an optimal action. Since the optimal action is output of information by voice, the contents of mail is read aloud. While, in this example, the apparatus B converts text data into voice format, when the apparatus B can not convert the data
15 the apparatus A may perform such conversion before the data output.

[Fifty-eighth Embodiment]

Fig. 149 is a diagram for explaining another pull task. In this example, an apparatus C is employed to
20 issue a command to an apparatus A. The apparatus A is a display, and an instruction "Display my schedule" is issued to the apparatus C. Although the communication is not specified in the instruction, it means that a user extracts schedule data from the apparatus B
25 (user's desktop PC) and displays it on the apparatus A.

While the information type is schedule information, the procedures for this is the same as

explained previously.

[Fifty-ninth Embodiment]

Fig. 150 is a diagram for explaining an example push task. In this example, an apparatus A that
5 receives a command is a scanner. The command shown in Fig. 150 is issued to instruct the apparatus A to transmit a document obtained by scanning to an apparatus B (printer) and to instruct the apparatus B to hold the document instead of printing it. This
10 session will now be described.

Fig. 151 is a diagram showing a session for the push task in Fig. 150. As is described above, the apparatus A is a scanner and the apparatus B is a printer.

15 The apparatus A performs the procedures in Figs. 138A and 138B while the apparatus B performs the procedures in Fig. 132. First, the apparatus A contacts the apparatus B to establish a connection for communication (step S1512). Assume that the response
20 is OK (steps S1524 and S1718).

Then, transfer of information (information <abc>) is requested. Since the request type is a request storage of information, the apparatus performs the procedures in Fig. 142. At the negotiation (step S1526
25 and S1913), the apparatus B requests the apparatus A for a format (<xyz>) of information to be transferred.

The apparatus A changes the format, if necessary,

and transmits the requested information (step S1527).
Upon the receipt of the information, the apparatus B
performs a required action according to the decision of
the transmission side, the user or the apparatus B.

5 The action is, for example, format conversion, filing,
index preparation, data extraction, or title
extraction. The necessary action in this embodiment is
to hold a received document instead of printing it.

[Sixtieth Embodiment]

10 Fig. 152 is a diagram showing another example push
task. The apparatus A, which is a scanner in this
example, sends a request to the apparatus B (scanner)
and the apparatus C (filing server) to push
information, to file a document on a reception side and
15 to extract its title and index.

The specific processing is the same as that in the
fifty-ninth embodiment. The session between the
apparatuses A and B will now be described while
referring to Fig. 153. The same thing is applied for
20 the session between the apparatuses A and C.
Communication between the apparatuses A and B and
communication between the apparatuses A and C are
performed in parallel.

Fig. 153 is a diagram showing an example push
25 session. The apparatuses A and B are scanners. when
the apparatus B receives data, it performs a required
action. In this case, the apparatus A transmits

information for designating an associated action that should be executed. The action is filing and extraction of a title and an index. While in this example the action is instructed from the apparatus A, 5 the apparatus B may decide an action, and may abandon a received action.

[Sixty-first Embodiment]

Fig. 154 is a diagram showing another example push task, which is a transmission of electronic mail. An 10 apparatus A (printer) at Kosugi is to transmit electronic mail "Get design from Bill" to an apparatus B (having a different network sub-domain from John's PC and the apparatus A) in New York.

Any method can be used for mail transmission. 15 First, when the apparatus A has a mail transmission function, it transmits the mail. If the apparatus A does not have such a function, it transmits mail information to another apparatus on the network, e.g., a mail server, and asks the mail transmission.

20 [Sixty-second Embodiment]

The instruction task INDICATE will be described while referring to Fig. 132. A user sends an instruction 93 to a copier 91 that is physically located in a remote area in order to permit a MyDesk 25 92, a desktop personal computer, to display the current location of the user.

The instruction 93 "Display present place on

4042227" E0808080

<MyDesk>", which is sent to the copier 91 that serves as the information processing apparatus 411, is transmitted from the operation unit 41 to the task reception unit 43. The contents are analyzed and
5 planning is performed on the results. Then, the execution unit 47 executes the final data as an instruction task INDICATE for a PC 92, which serves as the information processing apparatus 412 connected via the network.

10 The PC 92, which is the information processing apparatus 412 connected via the network, receives instructed information from the reception unit 43, analyzes a received instruction, and perform planning on the results. Then, the execution unit 47 displays
15 the location, such as "Now in conference Shimomaruko A111 conference room" on a screen.

Transmission of information for each session between the information processing apparatuses 411 and 412 will be explained while referring to Fig. 155.

20 Fig. 155 is a diagram showing transmission of information for each session between a copier, which serves as the information processing apparatus 411 for instruction task INDICATE, and a PC, which serves as the information processing apparatus 412.

25 The transmission side performs the processing in Figs. 139A and 139B, while the reception side performs the processing in Fig. 143. The communication contents

are an instruction and information for processing corresponding to the instruction. The transmission of information is the same as that in the above described push task.

5 In response to the instruction request from the apparatus A, the apparatus B transmits <xyz> instruction type that can be understood by the apparatus B. Upon receipt of the information, the apparatus A changes the instruction information, as
10 needed.

Then, the apparatus A issues, to the apparatus B, an instruction and necessary information to display on the PC screen the fact that a conference is being held and the current location. The apparatus B receives the
15 information, performs the process in consonance with the information, and displays the location of the user on the screen, as is instructed.

[Sixty-third Embodiment]

Another example instruction task INDICATE will now
20 be described while referring to Fig. 130. A user sends an instruction 71 to a copier 74 at a physically remote area in order to set a facsimile machine 75 at Shinkawasaki so that it transfers, to a printer 77 of Mr. Toyoda at Kosugi, a document that is received from
25 Mr. Suzuki.

The instruction 71 "Please advice MyFax to transfer any document sent from Mr. Suzuki to Mr.

Toyoda" which is sent to the copier 74 that serves as the information processing apparatus 411, is transmitted from the operation unit 41 to the task reception unit 43. The contents are analyzed and
5 planning is performed on the results. Then, the execution unit 47 executes the final data as an instruction task INDICATE for the facsimile machine 75, which serves as the information processing apparatus 412 connected via the network.

10 The facsimile machine 75, which is the information processing apparatus 412 connected via the network, receives instruction information from the reception unit 43, analyzes a received instruction, and perform
15 alters the condition setting. The transmission of information for each session between the information processing apparatuses 411 and 412 will be described while referring to Fig. 156.

Fig. 156 is a diagram showing transmission of
20 information for each session between a copier, which serves as the information processing apparatus 411 in this example instruction task INDICATE, and a facsimile machine, which swerves as the information processing apparatus 412. The transmission side performs the
25 processing in Figs. 139A and 139B, while the reception side performs the processing in Fig. 143. The transmission of information is the same as that in the

above described example.

In response to the instruction request from the apparatus A, the apparatus B transmits <xyz> instruction type that can be understood by the apparatus B. Upon receipt of the information, the apparatus A changes the instruction information, as needed. In this example, the apparatus A transmits to the apparatus B an instruction and necessary information to transfer, to Mr. Toyoda, a document that is transmitted from the Mr. Suzuki and addresses the user. Upon receipt of the information, the apparatus B performs the required processing in consonance with the information, and sets a designated condition.

[Sixty-fourth Embodiment]

An additional example instruction task INDICATE will now be described while referring to Fig. 135. A user sends an instruction 123 to a scanner 121 at a physically remote area in order to instruct a filing server 122 to transfer a stored document 125 "abc.doc" to John 124.

The instruction 123 "Action: SEND, What: r, From: Filing Server, To: John" which is sent to the scanner 121 that serves as the information processing apparatus 411, is transmitted from the operation unit 41 to the task reception unit 43. The contents are analyzed and planning is performed on the results. Then, the execution unit 47 executes the final data as an

instruction task INDICATE for the filing server 122, which serves as the information processing apparatus 412 connected via the network.

5 The filing server 122, which is the information processing apparatus 412 connected via the network, receives instruction information from the reception unit 43, analyzes a received instruction, and perform planning on the results. Then, the execution unit 47 transmits a document. The transmission of information
10 for each session between the information processing apparatuses 411 and 412 will be described while referring to Fig. 157.

Fig. 157 is a diagram showing transmission of information for each session between a scanner, which
15 serves as the information processing apparatus 411, and a filing server, which serves as the information processing apparatus 412. The transmission side performs the processing in Figs. 139A and 139B, while the reception side performs the processing in Fig. 143.
20 The transmission of information is the same as that in the above described example.

In response to the instruction request from the apparatus A, the apparatus B transmits <xyz>
instruction type that can be understood by the
25 apparatus B. Upon receipt of the information, the apparatus A changes the instruction information, as needed. In this example, the apparatus A transmits to

the apparatus B an instruction and necessary information to transfer, to John, a document "abc.doc" that is stored in the filing server.

Upon receipt of the information, the apparatus B
5 performs the required processing in consonance with the information, decides an optimal transmission method, such as E-mail, and transmits the document to John as is instructed.

[Sixty-fifth Embodiment]

10 Fig. 158 is a diagram showing an operation along the procedures of another apparatus. In the sixty-fourth embodiment explained while referring to Fig. 135, a user sends an instruction to the scanner 121 that is located at a physically remote area, in order
15 to instruct the filing server 122 to transfer the stored document 125 "abc.doc" to the John's desktop 124. And the scanner 121 interprets contents and executes the instruction task INDICATE.

In this embodiment, however, a printer 351
20 receives operation information 353 from a filing server 352 and displays it, and a user performs operation in accordance with the display and transmits the operation data to the filing server 352. In this manner, the same effect as in the sixty-fourth embodiment can be
25 obtained.

When a user requests the printer 351, which serves as the information processing apparatus 411, to operate

644221 20080608

the filing server 352, a planning decision unit 46 in the printer 351 makes a plan that necessary operation data 353 should be obtained to implement the operation procedures of the filing server 352. The process
5 execution unit 47 executes the information acquisition task PULL for the filing server 352, which is the information processing apparatus 412 connected via the network.

The filing server 352, which is the information
10 processing apparatus 412 connected via the network, receives instruction request information from the reception unit 43, analyzes a received request, and perform planning on the results. Then, the execution unit 47 transmits the operation data 353.

15 A screen is provided on the operation unit 41 of the scanner 351, which receives the operation data 353 from the filing server 352, and the operation unit 41 displays, on the screen, the procedures of the filing server 352 that correspond to the operation data 353.

20 According to the displayed operation screen, the information concerning the operation of the user is transmitted to the filing server 352 in the same manner. The filing server 352 that receives the operation of the user interprets it and performs a
25 necessary process. As a result, transmission of the file "abc.doc" to John, which is the object to the user, is enabled.

In the above description, the filing server 352 transmits the operation data 353 for implementing the operation procedures of the filing server 352; however, an operation data server may be prepared for managing the operation data 353, and may transmit the operation data 353. The operation data may also be transmitted from the third information processing apparatus that receives the operation data 353 of the filing server 352, like the printer 351 that serves as the information processing apparatus 411. The printer 351 may be replaced with a scanner.

[Sixty-sixth Embodiment]

Fig. 162 is a diagram showing the relationship between the change to three statuses of a print job and processes corresponding to the individual statuses. An output device (printer), which serves as the information processing apparatus 411, receives a print job that includes a document for which a user instructed printing.

First, an input job determination unit 391 determines whether a received print job should be immediately printed or should be held until a print execution condition is established. The result is transmitted to a pending job management unit 392 or an output wait job management unit 394.

The pending job management unit 392 stores the received print job as a pending job in a pending job

table 393. The pending job management unit 392 examines the pending job table 393 for the job for which print execution condition is established. If such a job is found, it is extracted from the pending
5 job table 393. The pending job for which the print condition is established is transmitted to the output wait job management unit 394.

The output wait job management unit 394 stores a received print job as an output wait job in an output
10 wait job table 395. When printing at the output unit 396 is enabled, the output wait job is extracted from the output wait job table 395 and transmitted to the output unit 396.

The output unit 396 prints the received job. When
15 printing is successful, the print job is transmitted to an output job management unit 397 to store the print job that has been output.

The output job management unit 397 stores, as an output job, the received print job that has been output
20 in an output job table 398.

As is described above, the received print job is changed into three statues and processed. The print execution condition of a pending job is not only a condition where the job is held until the user
25 instructs printing, but also a condition where printing is initiated at a designated time, or a condition where, if the main printer is other than printer A that

441221 "00000000

serves as the information processing apparatus 411, the main printer is ready for printing.

5 Figs. 163A and 163B are flowcharts showing the printing processing for this embodiment. The processing of a print task "PRINT (A, 'abc.doc')" or "PRINT (not A, 'abc.doc')" is performed when an instruction is issued to the printer A, which is the information processing apparatus 411, to print document "abc.doc" by the printer A and by a printer other than
10 the printer A.

When the print task PRINT is activated, at step S4001 a check is performed to determine whether or not a document to be printed is included in a print job. When there is no document to be printed, program
15 control moves to step S4002. At step S4002 a check is performed to determine whether the document is included among the documents in the print jobs that are entered in the pending job table 393, the output wait job table 395 or the output job table 398. When, at step S4003,
20 the document is not found, program control advances to step S4004.

At step S4004 the information acquisition task PULL is performed in order to acquire the document from another information processing apparatus 412. If, at
25 step S4005, it is ascertained that the document is successfully acquired, program control advances to step S4006. If the acquisition of the document fails,

program control moves to step S4016, whereat an error is displayed and another necessary process is performed. The processing is thereafter terminated. At step S4006 a check is performed to determine whether the document to be printed can be printed by the printer A, which is the information processing apparatus 411, or by a printer other than the printer A. If the conversion of the document into a printer description language is required, program control moves to step S4007.

At step S4007 a check is performed to determine whether or not the printer A, which is the information processing apparatus 411, can convert the document form. If the conversion is possible, program control goes to step S4008, whereat the document to be printed is converted into a suitable form. When the conversion is impossible, program control goes to step S4009, whereat instruction INDICATE is issued to another information processing apparatus 412 to convert the document to be printed. According to the instruction INDICATE, the information processing apparatus 412 may immediately perform the conversion and return the result, or may return only an acknowledgement and perform conversion after printing is instructed later.

At step S4010 a check is performed to determine whether or not the conversion result is successful. If it is successful, program control advances to step

S4011. If the conversion fails, program control moves to step S4016, whereat an error is displayed and another required process is performed. The processing is thereafter terminated.

5 At step S4011 a check is performed to determine whether or not the printer A, which is the information processing apparatus 411, should print a document. When it is determined the printer A should print the document, program control advances to step S4012, and
10 the document is printed. When the information processing apparatus 412 should print the document, program control goes to step S4013, and the information storage task PUSH and print task PRINT for the information processing apparatus 412 are performed.

15 At step S4014, whether or not the printing is successful is determined. When the printing is successful, program control advances to step S4015, and the print job is regarded as the output job, which is then stored in the output job table 398. The other
20 necessary process is performed, and the processing is terminated. When the printing fails, program control moves to step S4016, whereat an error is displayed and another required process is performed. The processing is thereafter terminated.

25 The conversion of the document at step S4008 includes a conversion of a normal text document into a document in a printer description language; a

conversion of a document in a specific printer language
into another printer language that the employed printer
can understand; a conversion of an image format
document read by a scanner or a digital camera into a
5 document in a printer language; or a conversion of a
document in the common language in WWW into a printer
language.

The conversion instruction INDICATE at step S4009
may be an instruction to the information processing
10 apparatus 412 that has a specific application to
convert a document in a language inherent to the
corresponding application into a document in a printer
language that can be printed; or an instruction to the
information processing apparatus 412 that has a
15 specific printing function to convert a document in a
language inherent to a specific printer into a document
in a printer language that can be printed.

Fig. 164 is a diagram showing the relationship
between the print job and the processing, which are
20 explained while referring to Figs. 162 and 163, and the
user's operation. When a user permits the scanner
A411, which serves as the information processing
apparatus 412, to read document "abc.doc" 144 and
issues an instruction "Send 'abc.doc' to printer B" the
25 printer B 412, which serves as the information
processing apparatus 411 that receives the print job,
does not print "abc.doc" immediately, but regards it as

a pending job and stores it in the pending job table 393.

When the user sends an instruction "Show pending documents" the document "abc.doc" is displayed on the operation panel of the printer B. Furthermore, when the user designates the document "abc.doc" and issues an erasure instruction "Delete pending document" the designated document is deleted from the pending job table 393.

When the user designates the document "abc.doc" and issues an instruction "Print pending document" the document "abc.doc" is changed to a print wait job, which is then stored in the output wait job table 395. When the printing is enabled, it is printed (415).

When the printing is successful, the document "abc.doc" is changed to the output job, which is then stored in the output job table 395. In addition, when the user designates the output document "abc.doc" and issues an erasure instruction "Delete printed document" the designated document is deleted from the output job table 398.

Fig. 165 is a diagram showing an example display screen that is used by a user to operate a print job in the three statues as explained in Fig. 162. In accordance with the operation by a user, an instruction from the information processing apparatus 412, or the result obtained by the process performed by the

information processing apparatus 411, the print jobs in the three statuses are operated arbitrarily, and are added as a new task to the task table 399.

For example, a user utilizes the operation screen
5 in Fig. 165 to delete (4209) a print job stored in the pending job table 393 (4201), to send (4208) the print job to print using another printer, or to print it immediately. It is also possible to instruct to increase the priority (4210) of a print job stored in
10 the output wait job table 395 (4202) so that it will be printed first, or a print job, or to print (4204) again the print job stored in the output job table 398 (4203).

The present invention can be applied either for a
15 system that is constructed by a plurality of apparatuses (e.g., a host computer, an interface device, a display) or for an apparatus including a single device.

The following is also included within the scope of
20 the present invention: in order to operate various devices to implement functions in the above embodiments, software program code for implementing the functions in the previous embodiments are supplied to a computer in an apparatus or in a system that is
25 connected to various devices, and in consonance with the program, the computer (or a CPU or an MPU) in the system or the apparatus operates the devices to

accomplish the functions in the above embodiments. In this case, the program code read from a memory medium accomplishes the functions of the above described embodiments. And the program code and means for
5 supplying the program code to the computer, e.g., a memory medium on which such program code is recorded, constitute the present invention.

A memory medium for supplying such program code can be, for example, a floppy disk, a hard disk, an
10 optical disk, a magneto optical disk, a CD-ROM, a CD-R, a magnetic tape, a nonvolatile memory card, or a ROM.

In addition, not only for a case where the functions in the previous embodiments can be performed when program code is read and executed by the computer,
15 but also for a case where, according to an instruction in the program code, an OS (Operating System) running on the computer, or another application software program, interacts with the program code to accomplish the functions in the above embodiments, this program
20 code can be included in the embodiments of the present invention.

Furthermore, the present invention includes a case where program code, read from a memory medium, is written in a memory that is mounted on a function
25 expansion board inserted into a computer, or in a function expansion unit connected to a computer, and in consonance with a program code instruction, a CPU

mounted on the function expansion board or the function expansion unit performs one part, or all of the actual processing in order to implement the functions in the above described embodiments.

- 5 When the present invention is applied for the above memory medium, program code corresponding to the previously described flowcharts is stored in the memory medium.

644227" 2026630